

Bid invitation

Information

Description:EMC/Water proofing items

Bid invitation number:6300031303

Bid invitation rules

Bid invitation currency: INR

Timezone: INDIA

Submission period: 18.02.2020 16:00:00

Opening date: 18.02.2020 16:00:00

Created On: 17.01.2020 08:22:06

Bid invitation text:

1. Payment term: 100% in 60 days after receipt and acceptance of material. In case of MSe category it is 30 days after receipt & acceptance of material.
2. Delivery Term : For BEML, KGF
3. Validity: 60days from the date of closing of tender.
4. Bidder to enclose MSe, SC/ST entrepreneur certificate etc. In the format available in collaboration folder.

Attachments:

Mse format

Digital Signature

Bid invitation details

Item	Product Price Condition	Description	Vendor product number	Delivery date/ performance period	Quantity
1	8700413275	INDUSTRIAL BITUMEN 85/125 GRADE BLOCK		00:00:00	1,000.000 KG

Item long text:

SPECIFICATION:(1)AS PER IS: 702: 1988: LS GRADE:85/125, SPECIFIC GRAVITY @27DEG.C MINIMUM:1.01-, FLASH POINT PENSKY MARTENS CLOUSED TYPE.DEG C MINIMUM:225, SOFTENING POINT DEG.C: 80 to 90, PENETRATION @ 25DEG C, 100g, 5SEC IN 1/100CM: 20 to 30, DUCTILITY @ 27DEG C IN CM MINIMUM : 3, LOSS ON HEATING, PERCENT BY WEIGHT MAX: 0.30, PERCENT BY WEIGHT SOLUBLE

Bid invitation

Information

Description:EMC/Water proofing items
 Bid invitation number:6300031303

Item	Product Price Condition	Description	Vendor product number	Delivery date/ performance period	Quantity
		IN CARBON-DISULPHIDE. MIN : 99.			
		OXIDISED BITUMEN FOR WATER PROOFING/OTHER APPLICATIONS.			
		Basic Price	INR		
		CGST - Central GST	%		
		IGST -Integrated GST	%		
		SGST - State GST	%		
		UTGST	%		
2	8700470005	SUPERTHERMOLAY APP (OR) EQUIVALENT		00:00:00	500.000 M2

Item long text:

SPECIFICATION:

APP BASED POLYMERIC MEMBRANE MINIMUM WEIGHING 3KG/SQ.MTS. AND MINIMUM 3MM THICK REINFORCED WITH POLYSTER NONE WOVE FABRIC (WEIGHT NOT LESS THAN 150 GMS PER SQ.MTS. PENATRATION @25 DEG. C: 25+/- 5 SOFTENING POINT DEG. CENT. >= 150 HEAT RESISTANCE: 120 DEG. CENT. TENSILE / LAP JOINT STRENGTH - A.LONGITUDINAL: 650 +/- 150, B.B. TRAVERSE: 450 +/- 100 COLD FLEXIBILITY DEG. CENT: -2 WATER ABSORPTION %: 0.2 ELONGATION% @ 23 DEG. CENT- A.LONGITUDINAL: 40 +/- 10, B.TRAVERSE: 50 +/- 10 PUNCTURE RESISTANCE - A.STATIC INDENTATION: L-3, B.DYNAMIC INDENTATION:

Basic Price	INR	
CGST - Central GST	%	
IGST -Integrated GST	%	
SGST - State GST	%	
UTGST	%	