












COPY RIGHT & CONFIDENTIAL THIS DOCUMENT IS THE EXCLUSIVE PROPERTY OF BEML & CONTAINS CONFIDENTIAL INFORMATION. THIS DOCUMENT OR ITS CONTENTS SHALL NOT BE USED, REPRODUCED OR DISCLOSED IN WHOLE OR IN PART, WITHOUT PRIOR WRITTEN PERMISSION OF BEML. THIS DOCUMENT & ALL ITS COPIES SHALL BE RETURNED TO BEML ON DEMAND DRAWING RELEASED FROM PLM, PHYSICAL SIGNATURE NOT REQUIRED

MACHINING DEVIATIONS FOR LINEAR DIMENSIONS	RANGE	0 - 6	6 - 30	30 - 120	120 - 315	315-1000	1000-2000	2000-4000	ABOVE 4000	RA
	TOLERANCE	±0.1	±0.2	±0.3	±0.5	±0.8	±1.2	±2	±3	~
FOR DIMENSIONAL TOLERANCES OF SHEET METAL PARTS AND WELDED STRUCTURES, REFER STD. RD-227										
UNSPECIFIED TOLERANCE FOR LINEAR AND ANGULAR DIMENSIONS REF. IS 2102 (PT-1) (MEDIUM)							QUALITY OF WELD JOINTS REF, RD 230 MEDIUM			
VALUES OF SURFACE TEXTURE SHALL BE AS PER COMPANY STD DS. 1012.C.							STATUS:			
WELDING SHALL BE CARRIED OUT AS PER IS: 9595-96										

DESCRIPTION : HOSE
TYPE : PP-6, O.D DIA8
MAKE : FESTO

UNCONTROLLED COPY

N1	0.025	▽
N2	0.05	▽
N3	0.1	▽
N4	0.2	▽
N5	0.4	▽
N6	0.8	▽
N7	1.6	▽
N8	3.2	▽
N9	6.3	▽
N10	12.5	▽
N11	25	▽
N12	50	▽
GRADE No.		
VALUE		
SYMBOL		
SURFACE ROUGHNESS		

SL.No.	QTY	PART / STOCK No.	DESCRIPTION				SIZE	COMPANY STD./I.S				Wt. (Kg)
								MATERIAL				
						PRODUCT	BMRCL METRO CARS					
						REF DRG						
						MATERIAL						
						HEAT TREAT.		APPD	MS		5/9/2018	
						SURFACE TREAT.		REVD	GD		5/9/2018	
						TITLE		CHKD	SK		5/9/2018	
						HOSE		DRWN	PR		4/9/2018	
							SCALE		SHEET	Wt.(Kg)		
ALT.NO.	ECN NO/CHANGES	DATE	BY	CHKD	APPD	 BEM LIMITED <small>NEW FRONTIERS. NEW DREAMS</small>	1:1		1 OF 1	0	DRG No. 926-60308	ALT
												



BEML LIMITED