

इंटरनेट

मानक

Disclosure to Promote the Right To Information

Whereas the Parliament of India has set out to provide a practical regime of right to information for citizens to secure access to information under the control of public authorities, in order to promote transparency and accountability in the working of every public authority, and whereas the attached publication of the Bureau of Indian Standards is of particular interest to the public, particularly disadvantaged communities and those engaged in the pursuit of education and knowledge, the attached public safety standard is made available to promote the timely dissemination of this information in an accurate manner to the public.

“जानने का अधिकार, जीने का अधिकार”

Mazdoor Kisan Shakti Sangathan

“The Right to Information, The Right to Live”

“पुराने को छोड़ नये के तरफ”

Jawaharlal Nehru

“Step Out From the Old to the New”

IS 1029 (1970): Hot-rolled steel strip (baling) [MTD 4: Wrought Steel Products]



“ज्ञान से एक नये भारत का निर्माण”

Satyanarayan Gangaram Pitroda

“Invent a New India Using Knowledge”



“ज्ञान एक ऐसा खजाना है जो कभी चुराया नहीं जा सकता है”

Bhartrhari—Nitiśatakam

“Knowledge is such a treasure which cannot be stolen”

BLANK PAGE



IS : 1029 - 1970
(Reaffirmed 1997)

Indian Standard

REAFFIRMED

~~2001~~

SPECIFICATION FOR
HOT ROLLED STEEL STRIPS (BALING)
(*First Revision*)

Sixth Reprint SEPTEMBER 2001
(Incorporating Amendments No. 1 and 2)

UDC 669.14-418.2-122.4

© *Copyright* 1975

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

**AMENDMENT NO. 3 NOVEMBER 2002
TO
IS 1029 : 1970 SPECIFICATION FOR HOT ROLLED
STEEL STRIPS (BALING)**

(First Revision)

(Page 3, clause 0.3) — Insert the following new clause after **0.3** and renumber the subsequent clause :

'0.4 For all the tests specified in this standard (chemical/physical/others), the method as specified in relevant ISO standard may also be followed as an alternate method.'

(MTD 4)

Reprography Unit, BIS, New Delhi, India

Indian Standard

SPECIFICATION FOR
HOT ROLLED STEEL STRIPS (BALING)
(*First Revision*)

Wrought Steel Products Sectional Committee, SMDC 5

<i>Chairman</i>	<i>Representing</i>
DR U. N. BHRANY	The Indian Iron & Steel Co Ltd, Burnpur
<i>Members</i>	
SHRI M. ANJANEYULU	Mining and Allied Machinery Corporation Ltd, Durgapur
SHRI D. P. SANYAL (<i>Alternate</i>)	
SHRI N. C. BAGCHI	National Test House, Calcutta
SHRI K. C. BANERJEE	Guest, Keen, Williams, Ltd, Calcutta
DR S. BHATTACHARYA	Directorate General, Ordnance Factories, Calcutta
SHRI D. SEN (<i>Alternate</i>)	
SHRI P. K. CHAKRAVARTY	The Tata Iron & Steel Co Ltd, Jamshedpur
DR G. P. CHATTERJEE	Indian Institute of Metals, Calcutta
SHRI B. N. DAS	National Metallurgical Laboratory (CSIR), Jamshedpur
SHRI D. M. DAYAMANA	Mukand Iron & Steel Works Ltd, Bombay
SHRI S. K. DAM (<i>Alternate</i>)	
MAJ-GEN M. G. DEWAN	The Tinplate Company of India Ltd, Golmuri (Tatanagar)
SHRI S. BALASHANKAR (<i>Alternate</i>)	
DIRECTOR (M & C)	Ministry of Railways
CHEMIST & METALLURGOIST, CHITTARANJAN LOCOMOTIVE WORKS (<i>Alternate</i>)	
SHRI K. C. GHOSH	The Braithwaite Burn & Jessop Construction Co Ltd, Calcutta
SHRI B. N. GUPTA	Steel Re-Rolling Mills' Association of India, Calcutta
SHRI S. BANERJEE (<i>Alternate</i>)	
SHRI HARCHAND SINGH	The Indian Steel and Wire Products Ltd, Indranagar
SHRI R. R. KAPLISH (<i>Alternate</i>)	
JOINT DIRECTOR STANDARDS (WAGON)	Ministry of Railways
JOINT DIRECTOR (IRON & STEEL) (<i>Alternate</i>)	
SHRI M. N. KHANNA	Hindustan Steel Ltd, Bilai
SHRI U. C. SHARMA (<i>Alternate</i>)	
SHRI D. P. LAHIRI	Ministry of Defence (R & D)
SHRI S. R. SAHAY (<i>Alternate</i>)	

(*Continued on page 2*)

IS : 1029 - 1970

(Continued from page 1)

<i>Members</i>	<i>Representing</i>
DR D. M. LAKHANI	The Indian Iron & Steel Co Ltd, Burnpur
SHRI K. H. SHARMA (<i>Alternate</i>)	
SHRI P. LAXMINARAYANA	Hindustan Shipyard Ltd, Visakhapatnam
SHRI G. S. LITTLEJOHN	The Metal Box Co of India Ltd, Calcutta
SHRI K. R. NARASIMHAN (<i>Alternate</i>)	
SHRI MOHAN PRASAD	Hindustan Steel Ltd, Rourkela; and Boilers Sectional Committee, EDC 40, ISI
SHRI DEEPAK CHATTERJEE (<i>Alternate</i>)	
SHRI P. R. NAIR	Iron and Steel Control, Calcutta
SHRI A. B. PANDA	Indian Engineering Association, Calcutta
SHRI E. ABRAHAM (<i>Alternate</i>)	
DR S. R. PRAMANIK	Hindustan Steel Ltd, Durgapur
DR B. R. DEORAS (<i>Alternate</i>)	
SHRI P. G. V. RAO	Inspection Wing, Directorate General of Supplies & Disposals, New Delhi
SHRI D. K. RAY (<i>Alternate</i>)	
SHRI D. V. REDDI	Ministry of Defence (DGI)
SHRI M. M. GUPTA (<i>Alternate</i>)	
SHRI I. M. SAKHUJA	Industrial Fasteners Association of India, Calcutta
SHRI M. M. MURARKA (<i>Alternate</i>)	
TECHNICAL ADVISER (BOILERS)	Central Boilers Board (Ministry of Industrial Development, Internal Trade & Company Affairs)
SHRI K. S. VAIDYANATHAN	M. N. Dastur & Co Private Ltd, Calcutta
SHRI R. K. SRIVASTAVA,	Director General, ISI (<i>Ex-officio Member</i>)
Deputy Director (Struc & Met)	
(<i>Secretary</i>)	

Indian Standard
SPECIFICATION FOR
HOT ROLLED STEEL STRIPS (BALING)
(*First Revision*)

0. FOREWORD

0.1 This Indian Standard (First Revision) was adopted by the Indian Standards Institution on 30 November 1970, after the draft finalized by the Wrought Steel Products Sectional Committee had been approved by the Structural and Metals Division Council.

0.2 This standard was first issued in 1956. As a result of experience gained during these years, it has been decided to cover the requirements for hot rolled strips of nominal thickness less than 3 mm and width less than 75 mm, known as baling hoop. The tolerance requirements for hot rolled strips have also been modified as per the manufacturing practice in the country.

0.3 This standard contains clauses which call for agreement between the purchaser and the manufacturer. Such clauses are **3.1, 8.1, 8.3 and 9.1** .

0.4 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS : 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard covers the requirements for hot rolled steel strips of three grades, soft, medium and hard, of a nominal thickness of less than 3 mm and width less than 75 mm, known as baling hoop.

2. SUPPLY OF MATERIAL

2.1 General requirements relating to the supply of hot rolled steel strips shall conform to IS : 1387-1967†.

* Rules for rounding off numerical values (*revised*).

† General requirements for the supply of metallurgical materials (*first revision*).

3. MANUFACTURE

3.1 The strips shall be manufactured from steel made by the open-hearth, electric, duplex, basic oxygen or a combination of these processes. In case, any other process is employed by the manufacturer, prior approval of the purchaser should be obtained.

4. CHEMICAL COMPOSITION

4.1 The ladle analysis of steel when made in accordance with IS : 228-1959* shall be as given below:

<i>Grade</i>	<i>Sulphur Percent Max</i>	<i>Phosphorus Percent Max</i>
Soft	0.060	0.060
Medium	0.060	0.060
Hard	0.050	0.050

4.2 Product Analysis — The product analysis shall be carried out on the finished product from the standard position. Permissible variation in case of such product analysis from the limits specified in 4.1 shall be as follows:

<i>Constituent</i>	<i>Variation Over the Specified Maximum Limits, Max</i>
	Percent
Sulphur	0.005
Phosphorus	0.005

5. MECHANICAL PROPERTIES

5.1 Sampling — One tensile test and two bend tests shall be conducted for every 10 tonnes or part thereof of the material of the same thickness and width. Test samples may be taken from either end of the strips and shall be at least 1.5 metres in length.

5.2 Tensile Test — The tensile properties obtained from test pieces, when tested in accordance with IS : 1663 (Part I)-1960†, shall be as specified in Table 1.

*Methods of chemical analysis of pig iron, cast iron and plain carbon and low-alloy steels (revised).

†Tensile testing of steel sheet and strip : Part I Steel sheet and strip of thickness 0.5 mm to 3 mm. (Since revised).

TABLE 1 TENSILE PROPERTIES

(Clauses 5.2 and 5.3.2)

GRADE	TENSILE STRENGTH kgf/mm ²	ELONGATION, <i>Min.</i> , FOR GAUGE LENGTH		BEND TEST (180°) INTERNAL DIA- METER OF THE BEND
		$5.65\sqrt{S_0}$ Percent	200 mm percent	
Soft	47 to 55	25	18	2t*
Medium	Over 55 to 63	22	15	4t
Hard	Over 63 to 70.9	15	12	4t

*t thickness of the strip.

5.3 Bend Test — Bend test shall be carried out in accordance with IS : 1692-1960*.

5.3.1 The bend test piece shall be cut so that the longer axis of the test piece is parallel to the direction of rolling.

5.3.2 The test piece shall be bent cold through 180°. The internal diameter of the bend for different grades of material shall be as given in Table 1. The test piece shall be deemed to have passed the test if the outer convex surface is free from cracks.

5.3.2.1 It is sometimes difficult to ensure that the material is accurately following the radius. In case of dispute, the test piece may be pushed into a block of lead by a former of appropriate diameter.

6. RETEST

6.1 Should any one of the test pieces first selected fail to pass any of the tests specified in this standard, two further samples shall be selected from the same lot for testing in respect of each failure. Should the test pieces from both these additional samples pass, the material represented by the test samples shall be deemed to comply with the requirement of that particular test. Should the test pieces from either of these additional samples fail, the material represented by the test samples shall be deemed as not complying with this standard.

7. FREEDOM FROM DEFECTS

7.1 The material shall be free from harmful defects.

*Methods for simple bend testing of steel sheet and strip less than 3 mm thick.

IS : 1029 - 1970

8. DIMENSIONS AND TOLERANCES

8.1 Unless otherwise specified, the hot rolled steel strips shall be supplied in dimensions as per agreement between the purchaser and the manufacturer.

8.2 Tolerance on thickness and width of the hot rolled steel strip shall not exceed the following limit:

	<i>Tolerance</i>
	mm
Thickness	± 0.16
Width	± 2

8.3 Unless otherwise specified, the hot rolled strips shall be supplied in lengths which shall be at the manufacturer's option subject to tolerances mutually agreed to between the purchaser and the manufacturer.

9. FINISHING AND PACKING

9.1 The requirements in regard to finishing and packing shall be subject to agreement between the purchaser and the manufacturer, but in the case of strips required for baling jute, they shall be lacquered.

10. MARKING

10.1 Each length of strip shall be marked indicating the size and grade of the material.

10.1. The product may also be marked with Standard mark.

10.2 The use of the Standard Mark is governed by the provisions of the *Bureau of Indian Standards Act, 1986* and the Rules and Regulations made thereunder. The details of conditions under which the licence for the use of Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

Telephones: 323 0131, 323 3375, 323 9402 Fax :+ 91 011 3234062, 3239399, 3239382

E - mail : bis@vsnl.com. Website : <http://www.bis.org.in>

Central Laboratory :

Plot No. 20/9, Site IV, Sahibabad Industrial Area, Sahibabad 201010

Telephone

477 00 32

Regional Offices:

Central : Manak Bhavan, 9 Bahadur Shah Zafar Marg, NEW DELHI 110002

323 76 17

*Eastern : 1/14 CIT Scheme VII, V.I.P. Road, Kankurgachi, KOLKATA 700054

337 86 62

Northern : SCO 335-336, Sector 34-A, CHANDIGARH 160022

60 38 43

Southern : C.I.T. Campus, IV Cross Road, CHENNAI 600113

254 13 15

†Western : Manakalaya, E9, MIDC, Behind Marol Telephone Exchange,
Andheri (East), MUMBAI 400093

832 92 95

Branch Offices:

'Pushpak', Nurmohamed Shaikh Marg, Khanpur, AHMEDABAD 380001

550 13 48

Peenya Industrial Area, 1st Stage, Bangalore-Tumkur Road,
BANGALORE 560058

839 49 55

Commercial-cum-Office Complex, Opp. Dushera Maidan, E-5 Arera Colony,
Bittan Market, BHOPAL 462016

72 34 52

62/63, Ganga Nagar, Unit VI, BHUBANESWAR 751001

40 36 27

5th Floor, Kovai Towers, 44 Bala Sundaram Road, COIMBATORE 641018

21 88 35

Plot No. 58, Neelam Bata Road, NIT, FARIDABAD 121001

542 82 61

Savitri Complex, 116 G.T. Road, GHAZIABAD 201001

471 19 98

53/5 Ward No.29, R.G. Barua Road, 5th By-lane, Apurba Sinha Path,
GUWAHATI 781003

54 11 37

5-8-56C, L.N. Gupta Marg, Nampally Station Road, HYDERABAD 500001

320 10 84

E-52, Chitrangan Marg, C- Scheme, JAIPUR 302001

37 38 79

117/418 B, Sarvodaya Nagar, KANPUR 208005

21 68 76

Seth Bhawan, 2nd Floor, Behind Leela Cinema, Naval Kishore Road,
LUCKNOW 226001

21 89 23

NIT Building, Second Floor, Gokulpat Market, NAGPUR 440010

52 51 71

Mahabir Bhawan, 1st Floor, Ropar Road, NALAGARH 174101

2 14 51

Patliputra Industrial Estate, PATNA 800013

26 28 08

First Floor, Plot Nos. 657-660, Market Yard, Gultekdi, PUNE 411037

426 86 59

'Sahjanand House' 3rd Floor, Bhaktinagar Circle, 80 Feet Road,
RAJKOT 360002

37 82 51

T.C. No. 14/1421, University P. O. Palayam, THIRUVANANTHAPURAM 695034

32 21 04

*Sales Office is at 5 Chowringhee approach, P. O. Princep Street,
KOLKATA 700072

237 10 85

†Sales Office is at Novelty Chambers, Grant Road, MUMBAI 400007

309 65 28