



**BEML LIMITED**  
(A Government of India Undertaking)  
206/D1,Bhagirathi,Rameshwaram Colony,  
Bariatu Road,Ranchi-834009  
Jharkhand, India

## **TENDER DOCUMENT**

**For**

### **Construction of Toilets and Renovation of Kokar Stores**

**Tender Document No. BEML/MKR/170/23/  
dated 16/01/2023**

**(Bid No. 6300038227 dated 16.01.2023)**

**DATE OF SUBMISSION 28.01.2023 BEFORE  
14:00 HRS**

#### **ISSUED BY**

The Regional Manager  
BEML LIMITED  
206/D1,Bhagirathi,Rameshwaram Colony,  
Bariatu Road,Ranchi-834009  
Jharkahnd, India

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

**TABLE OF CONTENTS**

Ref: BEML/MKR/170/23/

Date: 16/01/2023

Sub: Tender For “Construction of Toilets and Renovation of Kokar Stores.”

Sl. No.	Particulars	Page No.
01.	Table of Contents	2
02.	Invitation For Tender	3-5
03.	Details of Pre -Qualification and Technical Bid	6-10
04.	General details of the Firm	11
05.	Tender Conditions Acceptance Letter	12
06.	Undertaking	13
07.	Revised Tender and General Conditions	14
08.	General Conditions of Contract	15-26
09.	Special Conditions of Contract	27-39
11.	Particular Specifications	40-56
12.	Acceptable brands of Materials	57-58
13.	GST Rules	59-61
14.	Schedule A & B – Scope of Work	62-75
15.	Schedule C & D – Commercial Bid	76-87

**Note:**

1. The tenderer shall download the complete set of tender documents. The tender documents from Serial Page No: 01 to 87 shall be duly filled, signed along with the company seal, scanned and upload the requisite documents as per the technical bid in ‘C-Folder Technical Attachments’ in the SRM system.
2. Commercial bid shall be submitted on BEML SRM platform. You are requested to submit your final amount on SRM system Items tab (inclusive of all Taxes and duties) and the break-up details (Bill of Quantities) to be uploaded as per the price bid format attached at ‘Notes and Price Attachments’. Please note that the duly filled price bid format to be uploaded only in the ‘Notes and Price Attachments’ folder. The price break-up (Bill of Quantities) uploaded will be taken into consideration for the arrival of L-1 subject to arithmetical corrections if any.
3. If the attachment is uploaded in C folders technical bid attachments, **the bid will be summarily rejected.**
4. The Commercial bids of technically qualified tenderers/bidders shall be considered for opening.

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

**INVITATION FOR TENDER**

Sub: Tender For “Construction of Toilets and Renovation of Kokar Stores.”

\*\*\*\*\*

1. BEML Limited invites tenders for the subject work in Three bid system (Part ‘A’- Pre-qualification Bid, Part ‘B’-Technical bid & Part ‘C’-Commercial bid) through e- Tendering mode i.e BEML SRM platform.

**2. Earnest Money Deposit (EMD):**

a) EMD amount of Rs.48500/- (Rupees Forty Eight Thousand Five Hundred Only) (i.e. 2% of estimated tender value ) can be paid online or can be submitted in the form of Account Payee Demand Draft / Banker’s Cheque. Bidders exempted from Earnest Money Deposit (EMD) shall submit exemption certificate from competent authority.

**Online Payment of EMD amount can be made in our Bank account details below:**

**Beneficiary Name** : **BEML Limited**  
**Beneficiary Bank** : **State Bank of India**  
**Branch** : **Lalpur**  
**Account No** : **11048999662**  
**IFS Code** : **SBIN0012623**

Please ensure that online payment of EMD amount is made well ahead of the EMD Submission Date & Time mentioned in the Tender.

Or

**Payment of EMD amount through DD / Banker’s Cheque:**

b) EMD in the form of Account Payee Demand Draft (DD) / Banker’s Cheque for **Rs.48500/- (Rupees Forty Eight Thousand Five Hundred Only)** drawn in favour of BEML Ltd, Ranchi payable at Ranchi.

c) The above said Demand Draft DD / Banker’s Cheques/ EMD Exemption Certificate shall be submitted in **Sealed envelope** duly superscribing the **Bid Invitation No. 6300038227 dated 16/01/2023 Closing date 28/01/2023 Time 14:00 Hrs** at the top of the envelope. The words “**PRE-QUALIFICATION BID**” shall also to be written in bold letters at the top of the envelope. The name and address of the bidder shall be printed or written legibly on the left hand bottom corner of the envelope.

Please attach the details duly filled-up for refund of EMD amount (for bidders who do not qualify in the Technical Bid) in the following format along with the DD / Banker’s Cheque for EMD;

BANK NAME	
BRANCH NAME	
CITY	
IFSC CODE	
ACCOUNT NO	

**Signature of the Contractor(s) with seal**



**BEML LIMITED**  
(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

BENEFICIARY NAME	
------------------	--

- d) Bidders exempted from Earnest Money Deposit (EMD) shall submit exemption certificate from competent authority.
- e) The above sealed envelope has to reach the address as mentioned below on or before the closing date & time of the tender.

The Regional Manager  
BEML LIMITED  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

**General Instructions with regard to EMD:**

- a) Quotation submitted online without submission of EMD/EMD Exemption Certificate in-time will not be considered.
- b) EMD submitted in any other form will not be accepted and the offer is liable to be rejected.
- c) EMD lesser than Rs.48500/- (Rupees Forty Eight Thousand Five Hundred Only) will not be accepted and the quotation is liable to be rejected.
- d) EMD of technical disqualified bidders will be returned.
- e) EMD does not carry any interest on return.
- f) Pre-qualification and technical bids shall be opened **on closing date** i.e., **28/01/2023 @ 15.00hrs**
- g) No responsibility will be taken for postal delay or non-delivery/non receipt of EMD/firms claiming EMD exemption.

Tenderers shall ensure that, the Demand Draft/Bankers Pay Order towards EMD in original shall reach the above said office on or before the closing time of the tender.

Offers without EMD or EMD in the form other than the one specified or EMD with lesser amount shall not be considered and tenders will be rejected. No Interest would be paid on the Earnest Money Deposit.

**3. Completion Period:** The period allowed for execution of the work is **03 (Three) Months** from the date to be mentioned in the work order to be placed on the successful bidder.

**4.** Firms willing to participate in the tender may contact through e-mail: admin.srm@beml.co.in to obtain the user name and password for submitting the bids. The bidders have to submit their quotation ON LINE THROUGH SUPPLIER RELATIONSHIP MANAGEMENT (SRM) PLATFORM. All corrigendum, addenda, amendments, time extension etc., if any to the tender will be hosted on BEML website www.bemlindia.com only. Bidders shall regularly visit BEML's website to keep themselves updated. No separate advertisement shall be published in the newspaper in this regard.

**Signature of the Contractor(s) with seal**



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

5. Any queries/clarification / information / details regarding tender enquiry to be communicated only through email Id: [rm.mrp@beml.co.in](mailto:rm.mrp@beml.co.in), [mkr\\_hr@beml.co.in](mailto:mkr_hr@beml.co.in), [mr@beml.co.in](mailto:mr@beml.co.in) and queries/clarification/ information/details will be accepted up to 03 (Three) days prior to the closing date of the tender. Phone No: 0651-2544054, 0651-2544609, Mob.9571847371/7976016746.
  6. Any queries related to submission of quotation may please be communicated through e-mail: [admin.srm@beml.co.in](mailto:admin.srm@beml.co.in) or the bidder may contact BEML SRM team at Phone No.080-22963269, 22963141.
  7. **DIGITAL SIGNATURE:** To participate in this e-tender, the bidder shall have a valid class III Digital Signature issued by Authorized Certifying Authority to submit bid in our SRM e-procurement system.
  8. the quantities shown against each item are only approximate and hence any reduction / increase thereof during the execution of work shall not vitiate the contract. The company does not bind itself to accept the lowest or any other tender.
  9. The tender shall remain open for acceptance for a period of **90 days** from the date of opening of tenders.
  10. The tenderers shall visit the site and acquaint themselves with the conditions of the site prior to submission of tenders and no claims will be entertained later on the grounds of ignorance.
  11. Successful tenderer is required to employ qualified Engineer to supervise the work and they should be present when the work is under progress.
  12. The successful tenderer is required to sign the work order prepared based on the quoted rates placed on him by the Accepting Officer.
  13. The Accepting Officer reserves the right to place order as a whole or part of any item only as deemed fit.
  14. In case, the contractor / firm after quoting withdraw from the tender or refuse / delay in commencing the work or stop the work abruptly, their EMD will be forfeited.
  15. Bidders exempted from Earnest Money Deposit (EMD) shall submit exemption certificate from Competent Authority.
- Note:** Bidder shall ensure that their EMD (DD/EMD Exemption certificate) is dispatched well in advance so that it reaches this office before the time and dates stipulated. Request will not be entertained for late receipt.
16. Conditional tenders are liable to be rejected.

Thanking you

Yours faithfully,  
for BEML Limited

**Regional Manager**

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

**DETAILS OF PRE QUALIFICATION AND TECHNICAL BID**

Sl. No.	Item Description	Estimated Cost (In Rs. Lakhs)	EMD Amount (Rs)	Last date for submission of Tenders	Similar Nature of Work
				Date of opening of pre qualification bid	
				Date of opening of technical bid	
				Date of opening of commercial bid	
1.	Construction of Toilets at Kokar Stores (2 Gents, 1 Ladies & 5 Urinals)	Rs. 24.00 (approx.) Lakhs (Inclusive of all taxes & duties)	Rs 48500/-	28/01/2023 at 14:00 Hrs	Civil/Interior works
2.	Renovation of Kokar Stores Building & Boundary Wall.			28/01/2023 at 15:00 Hrs	
				28/01/2023 at 15:00 Hrs	
				Date of opening the commercial bids will be intimated to only the technically qualified Tenderers/bidders.	
		03 Months			

**Mode of submission and Documents**

Sl. No.	Nature of Bid	Mode of submission	Documents required to be submitted by the bidder
A	Pre-qualification bid	1. Online Payment of EMD amount  <b>OR</b> Payment of EMD amount through DD / Banker's Cheque to reach through Post/Courier to the General Manager, BEML LIMITED, 206/D1, Bhagirathi, Rameshwaram Colony, Bariatu Road, Ranchi-834009, Jharkhand, India  <b>OR</b>	EMD: Rs .48500/-  <b>OR</b> EMD Exemption certificate

**Signature of the Contractor(s) with seal**



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

		<p>Alternatively it can also be dropped in the Tender Box kept at Ground Floor, BEML Limited Bariatu Road, Ranchi.</p> <p>2.The sealed envelope of Prequalification bid will be opened on closing date <b>28/01/2023 at 15:00</b> Hrs in presence of the bidders, who wish to be present at the above venue.</p> <p>3.Pre qualification bid received late on account of any reason whatsoever will be rejected.</p>	
B	Technical Bid	<p>1) Through e-mode / BEML SRM Platform wherein Tenderers/bidders to submit their technical bids will be opened on closing date <b>28/01/2023 at 15:00</b> Hrs in presence of the bidders, who wish to be present at the above venue.</p> <p>2) However, technical bids of those firms who meet the pre-qualification criteria in all aspects will only be considered for further evaluation.</p>	<p>The complete tender documents shall be duly filled, signed along with the company seal, scanned and upload the requisite documents as per the Eligibility Criteria in 'C-Folder Technical Attachments' in the SRM system</p>
C	Commercial Bid	<p>1) Through e-mode / BEML SRM Platform.</p> <p>The commercial bids of only the shortlisted / qualified Contractors will be opened.</p>	<p>Commercial bid shall be submitted on BEML SRM platform. You are requested to submit your final amount on SRM system Items tab (inclusive of GST) and the break-up details (Bill of Quantities) to be uploaded as per the price bid format attached at 'Notes and Price Attachments'. Please note that the duly filled price bid format to be uploaded only in the 'Notes and Price Attachments' folder. The price break-up (Bill of Quantities) uploaded will be taken into consideration for the arrival of L-1 subject to arithmetical corrections if any.</p> <p>If the attachment is uploaded in C folders technical bid attachments, <b><u>the bid will be summarily rejected.</u></b></p>

**Signature of the Contractor(s) with seal**



**BEML LIMITED**  
(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

**ELIGIBILITY CRITERIA OF TECHNICAL BID**

In the Technical Bid, the firm has to furnish the following details / documents with regard to their experience etc:

**CREDENTIALS i.e., EXPERIENCE / FINANCIAL STATUS ETC.**

1. **Financial Position:** Average Annual financial turnover during the last Three (3) years, ending 31st March of the previous financial year, should be at least 30% of estimated cost i.e. **Rs. 720000/**

Details of Annual financial turnover during the last three (03) years, ending 31st March of the previous financial year.

<b>Financial Year</b>	<b>2019-20</b>	<b>2020-21</b>	<b>2021-22</b>
Annual turnover (Rs in Lakhs)			
Profit / Loss (Rs in Lakhs)			

**NOTE:** Copies of the Audited Balance sheet along with the Profit and loss statement for the last Three (03) years duly certified by auditor shall be scanned and uploaded along with the technical bid.

2. **Experience:** Experience of having successfully completed similar works (**Civil/Interior works**) during last Seven (07) years ending last day of month previous to the one in which applications are invited should be either of the following:
- (i) Three similar completed works costing not less than the amount equal to 40% of the estimated cost. (**i.e. Rs.960000/-**)  
**Or**
- (ii) Two similar completed works costing not less than the amount equal to 50% of the estimated cost. (**i.e. Rs 1220000/-**)  
**Or**
- (iii) One similar completed work costing not less than the amount equal to 80% of the estimated cost. (**i.e. Rs. 1920000/-**)

Details of having successfully completed similar works (Civil/Interior works) during last Seven (07) years ending last day of month previous to the one in which applications are invited from any Government/Public Sector Undertakings/Large Private Organizations with Certificates.

**Signature of the Contractor(s) with seal**





**BEML LIMITED**  
(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

Sl. No.	Name & Address of Client	Value of work & W.O. No.	Stipulated date of start	Stipulated date of completion	Actual date of completion	Completed value of work

**NOTE:** Copies of the completion certificate issued by respective clients shall be submitted along with the technical bid.

**3. Earnest Money Deposit:** You are requested to submit original Demand Draft/Bankers Cheque for Rs.48500/- (Rupees Forty Eight Thousand Five Only) in favour of "BEML LIMITED, Ranchi" payable at Ranchi, in a sealed envelope superscripting the name of work, towards Earnest Money Deposit along with the technical bid on or before the closing date & time of the tender to the office of "The Regional Manager, 206/D1, Bhagirathi, Rameshwaram Colony, Bariatu Road, Ranchi -834009, Jharkhand, India, " as part of the Pre-Qualification Bid.

Offers without EMD or EMD in the form other than the one specified or EMD with lesser amount shall not be considered and tenders will be rejected. No Interest would be paid on the Earnest Money Deposit.

Bidders exempted from Earnest Money Deposit (EMD) shall submit exemption certificate from Competent Authority.

**4. The bidders are required to mention and submit copies of the following:**

(i) Please quote your PAN/GIR No.  
(Registration Certificate of  
PAN/PAN Card/GIR issued by the IT Authorities  
shall be submitted along  
with the technical bid)

(ii) Please quote your ESI No.  
(Registration Certificate issued by the ESI Authorities  
technical bid)

**Signature of the Contractor(s) with seal**



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

(iii) Please quote your PF No.  
(Registration Certificate issued by the PF Authorities  
the technical bid)

(iv) Please quote your GST No.  
(Registration Certificate issued by  
the GST Authorities shall be submitted along with  
bid)

(v) EMD details: Amount, DD No & date

17. The commercial bids of the tenderer who have submitted the satisfactory documentary evidence for the above requirements shall be opened. The commercial bids of other tenderer i.e., who does not qualify in the Technical requirements will not be opened and EMD shall be refunded.
18. BEML Limited may ask for shortfall of documents during the evaluation of the technical bids. Request for shortfall documents and the response shall be through email only and no change in the prices of the bid shall be sought, offered or permitted.
19. **Please ensure that no price details are mentioned in the technical bid.** Offers with price details in technical bid (under Part II) will not be considered and their offer will be rejected.
20. The Commercial bids of only technically qualified bidders shall be opened subsequently.
21. **L-1 (lowest tender) will be arrived on total package basis only.** Package includes price for all particulars of work as detailed in scope of work.

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1, Bhagirathi, Rameshwaram Colony,  
 Bariatu Road, Ranchi-834009  
 Jharkhand, India

**DETAILS TO BE FILLED/ UPLOADED BY THE PARTICIPATING FIRM**  
 (to be given on the Firm's Company letter head)

Sl. No.	Description	Details to be filled/uploaded
1	Name of the Firm & Postal address for correspondence (With name of the Contact Person) with telephone number, fax and email id	
2	Bank Details like Bank account numbers & IFSC code with Banker's Name, Address & Contact No.:	Bank account numbers :- IFSC Code: Banker's Name :- Branch Name: Address :- Contact Number :-

I / we hereby certify that all the information given above is factual.

*Signature with date of Authorized signatory*

Name: \_\_\_\_\_

Designation: \_\_\_\_\_

Firm's Seal: \_\_\_\_\_

**Signature of the Contractor(s) with seal**



**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1,Bhagirathi,Rameshwaram Colony,  
 Bariatu Road,Ranchi-834009  
 Jharkhand, India

**TENDER CONDITIONS ACCEPTANCE LETTER**  
**(to be given on the Firm's Company letter head)**

To,  
 BEML LIMITED  
 206/D1,Bhagirathi,Rameshwaram Colony,  
 Bariatu Road,Ranchi-834009  
 Jharkahnd, India

Dear Sir,

**Sub: Acceptance of terms and conditions of the tender**

**Tender Reference No.** \_\_\_\_\_

I/We have downloaded / obtained the tender documents for the above mentioned "Tender/Work from the website(s) namely "Construction of Toilets and Renovation of BEML Kokar Stores ".

As per your advertisement given in the above mentioned website(s).

2.I/ We hereby certify that I/We have read entire terms and conditions of the tender documents from the page No.01 to 67 Which form the part of Contract agreement and I/we shall abide hereby the terms /conditions/clauses contained therein.

3. The corrigendum issued from time to time by your department/organization to have also been taken into consideration while submitting this acceptance letter.

4. I/We hereby unconditionally accept that the tender conditions of the above mentioned tender documents / corrigendum in its totality/entirety.

5. In case any provision of this tender are found violated, your department / organization shall be at liberty to reject this tender/bid including the forfeiture of the full said Earnest Money Deposit absolutely and we shall not have any claim/right against department in satisfaction of this condition.

Date:

Signature with date of Authorized signatory

Name: \_\_\_\_\_

Designation: \_\_\_\_\_

Firm's Seal: \_\_\_\_\_

**Signature of the Contractor(s) with seal**



**BEML LIMITED**  
(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

**UNDERTAKING**

**(to be given on the Firm's Company letter head)**

This is to certify that \_\_\_\_\_ (Name of the Firm) has not been banned / black listed / debarred from Trade by any Central /State Govt. Dept. / Autonomous Institution / PSUs in India as on the date of submission of the bid.

I / we hereby certify that all the information given above is factual.

Signature with date of Authorized signatory

Name: \_\_\_\_\_

Designation: \_\_\_\_\_

Firm's Seal: \_\_\_\_\_

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1, Bhagirathi, Rameshwaram Colony,  
 Bariatu Road, Ranchi-834009  
 Jharkhand, India

**REVISED TENDER AND GENERAL CONDITIONS**

To,  
 BEML LIMITED,  
 206/D1, Bhagirathi,  
 Rameshwaram Colony,  
 Bariatu Road,  
 Ranchi-834009

Sir,

I/We, the undersigned, do hereby tender to execute and fully complete the whole of the work set forth and described in the General Conditions, Specifications, Schedule of Prices and Bill of “Construction of Toilets and Renovation of BEML Kokar Stores”, in accordance with the terms, conditions and obligations therein contained.

I/We, further agree to add to or deducting from contract sum, as the case may require, The net value of all deviations (additions and deductions) including non tendered items, of the value of work completed, shall not exceed 20% of the approved contract value and 40 % in respect of any individual item, indicated in **schedule A & B -BOQ**. The value of such additions and deductions being calculated upon the prices for similar work set forth in the accompanying Bill of Quantities, or if similar work in the opinion of the Engineer in charge be not included in the Bill of Quantities then upon the price set forth in the Schedule of Prices attached hereto or as otherwise provided in the Clause-15 of the General Conditions.

I/We, also herewith send Rs \_\_\_\_\_ by online mode/Receipt/Draft as Earnest Money as required and to enter further into a contract with the Company for the execution of the said works in conformity with the aforesaid General Conditions, Specifications, both preliminary as well as Standard Schedule of Prices, and Bill of Quantities and the Drawing accompanying to all of which I/We hereby give.....assent and concurrence.

I/We, also undertake to complete and hand over the same in a satisfactory manner to the BEML Limited, or its authorized representative within the period stipulated from the date of commencement of the work in accordance with Para-8 of General Conditions of the Contract, signed, sealed and delivered by the said ..... this.....day of..... Two Thousand and..... in the presence of:

Yours faithfully,

(SIGNATURE)

**WITNESS:**

- 1.
- 2.

Home address of the Contractor/Business Address:

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1, Bhagirathi, Rameshwaram Colony,  
 Bariatu Road, Ranchi-834009  
 Jharkhand, India

**GENERAL CONDITIONS**

(UNDER WHICH THE WORKS HEREINAFTER DESCRIBED ARE TO BE PERFORMED)

**1. INTERPRETATION CLAUSE:**

In these General Conditions and the Specifications attached, the word 'COMPANY' shall be held to mean 'BEML LIMITED', the work 'CONTRACTOR' shall be held to mean one or more contractor or contractors jointly or generally engaged in the works to which these General Conditions and the specifications relate, and shall include his/their heirs, executors and administrators. The word 'ENGINEER-IN-CHARGE, shall be held to mean a Member of the staff of the BEML to supervise the work. The expression 'SITE OF WORKS, shall be held to mean the extent of land which the Company places at the disposal of the Contractor from time to time for the purpose of executing the contract works. The word 'DRAWINGS' shall be held to mean 'THE PLANS, SECTIONS, ELEVATIONS AND DETAILS OF WORKS' annexed to the contract and such further drawings, as the Engineer in charge may issue from time to time during the progress of the works and shall be held to include tracings and photographic prints. The word SPECIFICATIONS shall be held to include the tender General Conditions, Specifications, Schedule of Prices and Bill of Quantities.

**2. SUFFICIENCY OF PRICED BILL OF QUANTITIES AND TENDER:**

On the acceptance of this tender, the contractor shall forthwith satisfy himself as to the correctness and sufficiency of his tender for the works as well as all prices stated in the Bill of Quantities and the schedule of Prices and within SEVEN DAYS of the acceptance of his tender, he shall sign the contract which shall be construed and taken as an acknowledgement on his part of his complete satisfaction and acquiescence in the sufficiency of the prices. The amount of the tender shall be the sum at which the contractor engages to execute whole of the works set-forth in the Bill of Quantities, the contractor shall submit to the company, with his tender both Schedule of Prices and Bill of Quantities upon which the tender has been based fully and completely priced. Items left unpriced in the bill of Quantities shall be held to be included in the prices for other items of the work.

**3. CONTRACTOR TO EXECUTE CONTRACT WITH THE COMPANY:**

The successful contractor shall within SEVEN DAYS of the acceptance of his tender enter into and execute a formal indenture of contract to be prepared by the Company's Solicitor. The contractor shall not be entitled to make any charges for perusal of the contract.

**4. CONTRACT NOT TO BE ASSIGNED OR UNDERLET AND CONSEQUENCE OF GRATUITIES BEING GIVEN :**

The contractor shall not assign or make over the contract to any other person, or underlet it, or make a sub-contract with any workmen or workman for the execution of any part of work(s), but shall employ his own workmen for the labour thereof, who

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1, Bhagirathi, Rameshwaram Colony,  
 Bariatu Road, Ranchi-834009  
 Jharkhand, India

shall be paid by him in wages by the day. And in case the Contractor assigns or makes over the contract, or underlet or make sub-contract, contrary to this clause or either himself or his agents give any gratuity to any employee of the Company, the company shall be at liberty to terminate the contract.

**5. TENDER OR AGREED RATE :**

The contractor shall agree not to petition for revision of rates tendered for by him under any circumstances at any stage of the work, either during execution or when the final claims are settled.

6. In the event of anything evidently necessary to the due and complete performance of the works being omitted to be shown on the drawings or described in the specification or being omitted from the Bill of Quantities through oversight or error, the contractor shall, notwithstanding, execute (in the most perfect manner) all such works the same as if they had been severally shown, described and included without being entitled to make any extra claim or charge.

7. The contractor shall satisfy himself or shall be deemed to have satisfied himself as to the nature of the sub-soil, the three dimensions, levels, character and nature of all roads, existing drains, sewers, water, gas or other mains, electric cables and other things as regards any connection they may have with the works the subject of the contract, and he shall also inspect the site of the works and surroundings, the means of access there to and egress therefrom and shall generally obtain his own information on all matters and things which can in any manner influence his tender, No claims for extra works otherwise will be allowed in consequence of any misunderstandings, error or incorrect information on these points, or of any other inaccuracies in reference thereto, which may appear on the drawings, or in the specification, nor shall the contract be nullified in consequence of any such misunderstanding, error incorrect information or in-accuracies.

**8. ENGINEER IN CHARGE'S ORDERS TO COMMENCE WORKS AND AS TO NON-DELIVERY OF SITE :**

The Contractor having signed the contract, the Chief Engineer will forthwith give him notice to commence the works and the contractor shall upon receipt of such notice, commence the works and carry them on at such point and points and in such portions as the Engineer in charge may direct.

The Company shall, with the Engineer in charge written order to commence the works, give to the contractor, the use of so much of the site of works, as may in the opinion of the Chief Engineer be required in order to enable the contractor to commence and continue the construction of the works, and shall from time to time as works proceed give the contractor the use of such further portions of such site as the Engineer in charge may from time to time consider proper in that behalf, but the non delivery in manner aforesaid of the use of such site or any portion thereof shall not vitiate or affect the contract, nor any provision contained in the specification nor entitle the contractor to any increased allowance in respect of money.

**Signature of the Contractor(s) with seal**





**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1, Bhagirathi, Rameshwaram Colony,  
 Bariatu Road, Ranchi-834009  
 Jharkhand, India

**9. SETTING OUT WORKS AND NOTICES:**

The Contractor shall set out the whole of the works and be responsible for the correctness of the position, levels and dimensions of the several works, according to the drawings and written instructions of the Engineer in charge. If at any time during the progress of the works any error shall appear or arise in the position, levels or dimensions of the several works, the contractors on being required to do so by the Engineer in charge, shall at his own expense remove and amend the works to the satisfaction of the Engineer in charge, notwithstanding that he may have been assisted by Engineer-In-Charge in setting out the same. The contractor shall observe, perform and comply with the requirements of all statutes and byelaws and shall also serve notice on the authorities having control of the road surfaces before the same are broken up and he shall likewise serve notices on the owners of the sewers, drains, water, gas or other mains, electric cables and other things which may be in any way affected by the execution of the contract work.

**10. TIME OF WORKING (APPLIES ONLY FOR FACTORY AREA):**

As the entry and exit of the workmen into the factory area is controlled by the Security Authorities of the Factory, the contractor should strictly adhere to the timings of entry and exit, laid down by the authorities and the rates quoted are deemed to include for this provision.

**11. NIGHT WORKS:**

The works shall be carried on day and night continuously without extra charge. If bad or treacherous ground be met with or if there be any other causes whatsoever, which in the judgment of the Engineer-In-Charge, requires, it, but no work shall be carried on in the night without the knowledge and sanction of the Engineer-in-charge.

**12. PROVISIONS TO BE MADE BY THE CONTRACTOR :**

The Contractor, shall at his own cost provide keep all open trenches, excavation or other dangerous places properly and sufficiently lighted between sunset and sunrise, and shall provide and fix proper fencings and boarding and temporary bridges to protect and assist the public traffic. The contractor shall also at his own cost erect temporary fences on the site of works where required by the Engineer-in-charge.

**13. TEST MATERIALS :**

All the materials to be used in and on every part of the works shall be subjected from time to time to such tests as the Consultant and Engineer in charge may direct. Such tests shall be performed at the expense of the contractor but the Company shall refund to the Contractor the actual cost of testing any of the materials which are proved to conform with the conditions of the specifications but the samples shall be, in all cases, selected by the Engineer in charge, and supplied by the contractor as part of the contract. If, at any time, any materials so tested is not equal to the test for such materials, hereinafter specified, the same shall be removed from the site of works, and other

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

materials substituted therefor, but in the absence of any specified test, the decision of the Engineer in charge, shall be final as to whether the said material or materials shall be used in the works, or forthwith removed and other materials substituted.

### **14. MATERIALS, TOOLS ETC., BROUGHT ON TO WORKS TO BECOME PROPERTY OF COMPANY DURING CONTINUANCE OF CONTRACT:**

All materials, tools, implements and other things brought by the Contractor upon Company's works shall there upon become and shall continue to be the absolute property of the Company and be considered in its possession, the Contractor having only the right of using the same for the purpose of the contract. After the works have been completed and all obligations under the contract duly fulfilled, the Company shall return to the Contractor the tools, implements and surplus or waste materials then remaining upon the Company's works to be removed by him forth-with and cleared away. Nevertheless, the Company shall not at any time be liable for the loss of any of the said materials, tools, implements or other things but the whole of this liability shall fall upon the Contractor, the same as if they had remained in his possession.

### **15. POWER TO VARY WORKS:**

The Company shall have full power and authority from time to time, and at all times, to order works additional to the contract, and to make and issue such further drawings and to give such further instructions and direction as may appear necessary or proper for the guidance of the contractor and the good and sufficient execution of the contract, and the contractor shall receive, execute, obey and be bound by the said further drawings, instruction and directions, according to the true intent and meaning thereof and as fully and effectively as though they had accompanied, or had been mentioned or referred to in the original drawings and specifications. The company shall also have power to vary or alter the levels or position of any of the works, the subject of this contract, or may order any of the works contemplated thereby to be omitted with or without the substitution, of any other works in lieu thereof, or may order any work, or any portion of work executed or partly executed, to be removed, changed or altered, and if needed that other work shall be substituted in lieu thereof and the difference of expense occasioned by any such increase, diminution or alterations so ordered and directed shall be added to or deducted from the amount of the contract agreeable to the prices for similar works set forth in the Bill of Quantities, or failing which the Schedule of Prices attached hereto, and in the absence of any such similar work being scheduled, the Engineer in charge shall determine the amount to be paid for such additions or deductions. The company will in no case become liable to the payment of any charge in respect of any such conditions, alteration or deviations, unless the instructions for the performance of the same shall have been given in writing and signed by the Engineer in charge, nor unless such instructions distinctly states that the matter thereof is to be subject of an extra or varied charge, in the form of an order hereinafter set forth nor unless the claim thereof shall be made in writing, signed by the Contractor and in the form of claim herein as set forth and properly filled up nor unless such claim be made within the week in which the work is executed and materials used, and before the same shall have been placed out of view, or beyond check of measurement, nor unless the value of any altered or varied works, or any further works shall wherever practicable have been determined and settled before such altered, varied or further works shall have been commenced. Such value in case of dispute shall be ascertained by the Engineer in charge, who shall determine in all cases whether such

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

previous determination and settlements were practicable or not, and in all the cases where he shall consider the same to have been practicable, the contractor shall not be entitled to make any claim in respect of such altered, or varied or further works if it shall, in the opinion of the Engineer in charge, if any special instance become necessary to execute any additional or substituted work, either wholly or in part by the day the claim therefor, shall not be recognized unless the contractor shall have delivered to the Engineer-in-charge, within one working day, and so on from day to day a true and exact list of the name, occupations, time and wages of the several workmen engaged during the previous day on any and every such works in respect of when a charge 'BY THE DAY' is intended to be made in the next succeeding weekly claim of contractor, Nevertheless, no charge 'BY THE DAY' shall be made unless, in the opinion of the Engineer in charge, it is impracticable or unreasonable to determine the value of the amount of work in manner otherwise provided for in these general conditions. All such instruction given by the Engineer in charge, shall be in the following form or as near there to as may be:

ORDER No:

CONTRACT No.

In pursuance of clause-15 of the General Conditions of contract and subject as there in mentioned, we request you to perform the under mentioned at the under mentioned price, namely :

SUCH WORK  
BEING INADDITIONAL TO  
SUBSTITUTION FORWORK INCLUDED  
IN THE

tender, and we request you to omit the under mentioned work at the under mentioned prices, viz.

DATE:

SIGNATURE OF THE  
ENGINEER-IN-CHARGE.

AND every claim shall be made in the following form:

CLAIM No: \_\_\_\_\_ CONTRACT No. \_\_\_\_\_

Contractors claim under and subject to Clause-18 of the General Conditions of Contract for the week ended Saturday the \_\_\_\_\_ day of \_\_\_\_\_ in respect of other than contract work.

Work Claimed For		Number Of Engi- neer's Order	Price of Similar Work in Bill of Quantity of Schedule.		Where no Similar Work in Bill of Quantity Of Schedule.	Amount claimed Rs.
Quan- tity in Mtrs.	Des- crip- tion.		Number/ Number of items	Value of Item.		
					Schedule Price of Labour.	

DATE:

SIGNATURE OF THE CONTRACTOR 'S

The claim shall be delivered to the Engineer-in-charge, for his examination before being transmitted by him to the Chief Engineer and shall be subject in all respect to

**Signature of the Contractor(s) with seal**



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

the consideration, ratification and correction of the Chief Engineer who shall be at liberty to decide whether any such claim entitle the Contractor to any, and if so, what extra charges, according to the true meaning and intention of the specifications, and whether any and what allowance shall be made to the company in respect of any work or obligation to be performed under the contract and from the performance of which the contractor may be or become directly or consequently relieved by reasons of any such additional or substituted works.

### 16. **SUSPENSION OF WORK:**

The Contractor(s) shall suspend the execution of work or any part or parts thereof whenever called upon in writing by the Chief Engineer to do so and shall not resume work thereon until so directed in writing by the Chief Engineer. The Contractor will be allowed by the Chief Engineer an Extension of time (not less than the period of suspension) for completion of the item or group of items of work for which a separate period of completion is given in the contract and of which the suspended work forms part but not other claims in this respect for completion or otherwise, however, shall be admitted. The contractors shall have no claim to any payment of compensation or otherwise, whatsoever on account of suspension of work.

### 17. **WORKS TO BE EXECUTED IN APPROVED MANNER:**

The works, the subject of the contract, specified and provided for or that they may be necessary to be done to form and complete any part thereof, shall be executed and completed in the best substantial manner, with materials of the best and most approved quality of their respective kinds agreeable to the particulars contained in or implied by the specification or as referred to and represented by the drawings and memoranda thereon or as referred to by any of the said further drawings and memoranda thereon or as referred to by any of the said further drawings, instructions and directions and shall be to the full satisfaction of the Engineer in charge, . The Engineer in charge, shall have full liberty at all reasonable time to inspect and examine the works, materials and workmanship, and may every such time reject any or all of such works, materials and workmanship which to him/them or either of them may appear defective, unfit or improper for the several purposes to which they are applied, or intended to be applied, or as not in accordance with the specification or the said drawings, memoranda, instruction or directions respectively.

### 18. **WORK TO BE CARRIED ON WITH EXPEDITION FAILING WHICH THE COMPANY MAY EMPLOY OTHER CONTRACTOR WITHOUT VITIATING THE CONTRACT:**

The Contractor shall commence to carry on the works with due diligence, and as such expedition as the Engineer in charge, may reasonably expect, having regard to the specified time of completion of the whole of the works. In case the contractor fails to do so, or neglect to provide proper and sufficient materials, or to employ a sufficient number of workmen to execute the work, then the company shall have full power, without vitiating the contract, to take the works wholly or in part out the hands of the contractor to engage or employ any other person or workmen to procure all requisite

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

materials and implements for the due execution and completion of the said works, and the cost and charges incurred by the company in so doing shall be ascertained by the Chief Engineer and be paid for or allowed to the company by the contractor and it shall be competent for the Company to deduct the amount of such costs and charges along with overheads out of any sum or sums due or to become due from the company to the contractor under this or any other contract.

### 19. INFERIOR MATERIALS OR WORKMANSHIP TO BE AMENDED :

The materials as well as the workmanship and finish of the whole of the contract works shall be best of their kind and should any materials be brought upon the site of works or on any land or property of the company or on the places where the operations are being carried out in connection with the works, which in the judgment of the Engineer in charge, is of an inferior description and improper to be used in works, the said materials shall be removed. All inferior workmanship or finish shall be amended by and at the cost of the contractor forthwith, or within such period or periods as the Engineer in charge, may direct, and the contractor shall pull down, amend and reconstruct any work he may have erected upon an insecure or insufficient foundation or that he may have insufficiently secured and protected against immediate and future injuries, whether arising or likely to arise in future from weight, pressure action of water or otherwise, on being required to do so by the Engineer in charge. In case the contractor neglects or refuses to remove such materials or comply with such directions it shall be lawful for the Chief Engineer, on behalf of the company and by its agents, servants and workmen to remove the materials and amend the workmanship and finish, so objected, to, or any part thereof, and to replace the same with such other materials, workmanship and finish as shall be satisfactory to the company and on the certificate of the Chief Engineer to deduct the expense thereby incurred, or to which the company may be put or be liable or which may be incidental thereto, from the amount of any sum or sums due to or become due to contractor, or to recover the same by action at law or otherwise from the contractor as the company may determine.

When it is apparent to the Chief Engineer that defects exist in the work, or that damage or accident has occurred to the works, or that the works are not upheld or maintained in good sound and water tight conditions, or repair or in working order, but the cause thereof is not apparent, a general requisition in writing by the Chief Engineer to the contractor to amend, make good or maintain the works in sound, perfect and water tight conditions shall be under no obligation to specify the work or repair, but such requisition shall be conclusive evidence against the contractor that he is not performing his obligations under the contract.

### 20. EMERGENCY POWERS :

In the event of any accident or failure occurring in or on the works, which, in the opinion of the Chief Engineer requires immediate attention either during construction or during the period of maintenance the company may by their own or other workmen make necessary repairs at the expenses of the contractor.

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

### 21. **OPENING TO BE MADE FOR EXAMINATION OF WORKS:**

Should Engineer-in-charge require it for their more perfect satisfaction, the contractor shall at any period during the **continuance of the contract**, pull down any part of the work and make such openings, as to such extent through any part of the said work as the Engineer-in-charge, may direct and the contractor shall make such works good again to his or their satisfaction. Should the work be found faulty in any respect, the whole of the expenses thereby incurred shall be defrayed by the contractor but if otherwise by the company.

### 22. **PRECAUTIONS AGAINST INJURY TO PROPERTY ADJACENT TO THE WORK IN PROGRESS:**

The contractor shall take special care, by the erection of temporary fences and by every other means which circumstances may render necessary, to prevent all injury and damage to or trespass upon the lands, roads, fences or property adjacent to the site of works and shall confine the passage of his workmen to existing public roads, foot paths. He shall likewise pay and satisfy all claims whatsoever and from whomsoever, for temporary occupation, way-leaves, damages, the trespass or otherwise, in reference to the said lands, roads, fences and property adjacent and bear the company harmless from any and all such claims. If any greater extent of land than the site of work be required by the contractor for his operations, he shall obtain and occupy the same at his own cost and charge.

### 23. **PRECAUTIONS AGAINST ACCIDENTS OR INJURY:**

The Contractor shall, at his own expense, shore, sling, protect, support, alter, restore make good and maintain as may be necessary, all buildings, water and gas pipes, sewers, drains, electric cables and other things which may be disturbed, exposed or injured during the execution of works or in consequence of the execution of the works and shall also provide any extra timbering which may be temporarily required and all labour in fixing and removing the same and shall, at his own expenses provide for the continuous use of all buildings, pipes, sewers, drains electric cable, water sources and other things, the use of which may be liable to interruption during the progress of the work. The Contractor shall at his own expense restore all such buildings, water and gas pipes, sewers, drains, electric cables and other things to the satisfaction of the owners thereof and he shall like wise, at his own expense, construct and maintain such works as may be necessary for the due permanent support of all such buildings, pipe, sewers, drains, electric cables and other things met with in the construction of works, and shall indemnify, save, harmless and keep indemnified, the Company and its officers from and against all action, suits, claims, penalties, liabilities, cost, expenses and demands whatsoever, by reasons or on account of damage to such buildings, pipes, sewers, drains, electric cables and other things whether caused by the execution of the contract works or in the insufficiency of the aforesaid permanent support. The Company may deduct the expenses thereby incurred or to which the Company or its Officers may thereby be put or be liable or which may be incidental thereto from, the amount of any sum or sums due or to become due to the contractor or may recover the same by action at law or otherwise from the contractor and the Company may

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

compromise any such action suits or other proceedings, or such terms as it shall see fit and contractor shall thereupon forthwith pay the Company the sum or sums paid by the Company upon the occasion thereof, and shall in every case pay such sum or sums as shall fully indemnify the Company according to the present stipulation.

**24. COVERING OF CONSTRUCTION SITE:**

The Contractor shall, at his own expense, make arrangements to cover/wrap the construction site in mesh material of green color to prevent the dust from the escaping into the adjoining Properties or premises and atmosphere and also to prevent accidental fall of debris onto the people. The contractor at his own expense should make arrangements to remove the cover after completion of the work.

**25. ROYALTIES:**

The Contractor shall be liable to pay all royalties chargeable on Government or Company materials required for the work.

**26. REJECTED MATERIALS:**

All rejected materials will at once be removed from site by the contractor to such distance as may be desired, failing which the company after giving three days notice in writing may do so and recover the cost of removal from the contractor.

**27. COMPANY'S PLANT:**

No Company's plant, materials or Labour will ordinarily be lent or hired to the contractor. Exceptional cases must have the approval of the company in writing.

**28. SCOPE OF COMPLETION:**

Completion includes completion of all work in accordance with the plans and specifications, removal of all yard mess accumulated during construction, levelling and cleaning up the site and generally cleaning the whole building or works.

**29. FINAL MEASUREMENTS TIME:**

The final measurement must invariably be preceded by a thorough remeasurement of the whole of the work, performed which will be made by the company's authorized representative and at which the contractor or his accredited agent must be present. For this purpose, a written notice will be sent to him at least THREE DAYS before the date fixed for the measurements, appointing the day, hour and place of meeting. Should he not attend to this the measurements will proceed without him, and he will be precluded from making any protest.

- 30.** If a dispute arises between the company and contractor as to the quantity or quality of work, performed, involving sum larger than Rs.500.00, the contractor may appeal in writing to the company for remeasurement or reappraisal, as the case may be. If the company considers that Contractors claim is valid, they may appoint an officer, other than the Officer who made the final measurement and inspection vide Paragraph-28

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

above, and his report shall be considered as final and binding on the contractor. The Contractor shall have a representative present when the remeasurement or the appraisal is being made.

### 31. ATTENTION:

- i) Time will be the essence of the contract and the contractor is to complete the whole of the work in the time stated in the tender, subject to the schedule of conditions.
- ii) The contractor is to provide at all times during the progress of work and the maintenance period proper means of access, with ladders, gangways, etc., and the necessary attendance to move and adopt as directed for the inspection of their representative (no separate rate will be allowed).
- iii) The Contractor is to keep all persons under his control and within the boundaries of the site and he will be held responsible for the care of the works generally until their completion including all works executed and materials deposited in the sites by himself or suppliers, together with all risks arising from weather, carelessness of operatives, damages or loss by thefts or by any other cause, and is to allow for all necessary watching and protective lighting.

### 32. LABOUR ACTS:

- i. The Contractors shall employ labour in sufficient number to achieve the required rates of progress and quality to ensure best workmanship of the degree required under various specifications and to the satisfaction of Engineer-in-charge. The contractors shall remain liable for the payment of all wages or other remunerations to his labourers or employees under the Payment of Wages Act 1936, Minimum Wages Act 1948, Employers liability Act 1938, Workmen's Compensation Act 1923, ESI Act 1948, or any other Acts or enactments relating there to and rules framed there under from time to time. In the event, the contractor fails or neglects to pay any amount due by him under the workman's compensation Act, ESI Act or other Labour Laws, the Company is entitled to withhold the same from any other amount payable by it to the contractor and remit the same to the authority concerned and such payment shall be binding on the contractor.
  - i) In the event of contract, the contractor shall be responsible for implementing the provision of the contractor Labour Act in to and also responsible for any repercussions arising there from for non-compliance thereof.
  - ii) The intending tenderers should quote their organization registration/code numbers for the registration with ESI/PF Authorities. It may be noted that other things being equal, preference will be given in the acceptance of tender to firms having independent registration with ESI/PF Authorities.
  - iii) BEML shall arrange to recover from the contractors bills requisite amounts of both Employer's and Employee's contribution for both ESI and PF calculated

***Signature of the Contractor(s) with seal***





## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

on the basis of 25% of the value being taken as the labour cost and recover such amounts from the respective bills and keep the same in suspense account. On production of requisite documentary evidence supporting payment of ESI/PF Authorities/supported by the acquaintance rills, the amount earlier recovered from contractor's bills shall be paid duly adjusting the shortfall in remittance, if any.

- iv) In the event of any accident/injury/disablement, the contractor shall arrange to pay the requisite compensation legally payable to the concerned employee/dependents and also indemnify to BEML in case of any claim arising therefore later.
- v) CONTRACTOR should employ only ESI Registered workmen on any item of work. If contractors have workman who have not yet been Registered under the ESI they should ensure that the workers have been duly registered before employing them in work.
- vi) CONTRACTORS should produce his MUSTER ROLL duly certified by Engineer-in-charge once in a month say before 5<sup>th</sup> of each month to the Pay roll section, so that the ESI amount can be ascertained and recovered/payment obtained irrespective of the fact whether work order is issued or not.
- vii) If there is any default on the part of the contractor, an estimated amount towards ESI liability including the would be penalty/damage, will be recovered by the company from the bills of the contractors.
- viii) CONTRACTORS should maintain all registers and records required for ESI, PF Payment of wages, etc., under the statutes and produce them for verification as and when called for by company inspecting Authorities.
- ix) THE contractor shall disperse the wages to the workmen in the presence of the authorized representative of the company.
- ii. CONTRACT Labour (Regulation and Abolition) Act 1970 under section 12 and Rule 21 prescribes that every contractor who employs labour for executing contract works should obtain license from Labour Authorities to carry out any works contract, so that the labourers employed by the contractor are not deprived of the facilities provided under the Act. Such license shall be produced to BEML Authority before commencement of the work.

### **33. TRAINING APPRENTICES:**

The CONTRACTOR shall comply with the provision of the Apprentices Act 1961 and the rules and order issued there under from time to time. If he fails to do so his failure will be a breach of contract and the Accepting Officer may in his discretion cancel the contract. The contractor shall also be liable for any pecuniary liability arising on account of any violation by him of the provision of the Act.

***Signature of the Contractor(s) with seal***



## **BEML LIMITED**

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

### **34. FAIR WAGES:**

The Contractor shall not pay less than fair wage to labourers, workmen engaged by him on the work. Fair wages means wage for the various categories of labour, workmen, fixed from time to time by the labour authorities of the area. The contractor shall ascertain the minimum fair wages prevailing in the area before submitting his tender. The Contractor should also abide by labour regulations in regard to the payment of wages, wage period, fines and deductions from wages, maintenance of wage book, wage slip, publication of scales of wage and other terms of employment, inspection and submission of periodical returns and all other matter relating to labour rule in force.

### **35. DISPUTE RESOLUTION AND JURISDICTION:**

All disputes or differences whatsoever arising between the parties out of or relating to the construction, meaning and operation or effect of the contract or the breach thereof arising during the progress of work or after completion or abandonment thereof shall be mutually discussed and settled amicably by conciliation Committees/ Councils comprising of independent subject experts constituted by BEML, failing which, the dispute shall be settled by arbitration consisting of sole arbitrator appointed by the Company in accordance with the provisions of Arbitration and Conciliation Act 1996 and the arbitration proceedings shall be conducted at the place of awarding of original contract.

The court at the place of awarding of contract only shall have jurisdiction to entertain any dispute/matter relating to the contract

In case of any dispute between the Company and any other Public Sector / Government department relating to the interpretation and application of the provisions of the contract, such disputes / differences shall be referred by either party to the arbitration of one of the arbitrators in the Department of Public Enterprises. The Arbitration and Conciliation Act, 1996 and amendment thereof shall not be applicable to this clause. Any party aggrieved by such award, shall make further reference to the Ministry of Law and Justice, Government of India.

In case BEML challenges the Arbitral Award passed against it, 75% of the award may be paid to the contractor / concessionaire against Bank Guarantee without prejudice to the final order of the Court in the matter under challenge. The payment may be made into a designated Escrow Account with the stipulation that the amount so released will be used, first, for payment of lenders' dues, second, for completion of the project and then for completion of other projects of BEML, as mutually agreed / decided. Any balance remaining in the Escrow Account subsequent to settlement of lenders' dues and completion of projects of BEML, may be allowed to be used by the contractor / concessionaire with the prior approval of the lead banker and BEML.

In case the subsequent court order required refund of the money paid by BEML to the contractor / concessionaire against Bank Guarantee, the amount shall be refunded by the contractor / concessionaire along with appropriate interest. The rate of interest on such refund amount shall be decided by BEML keeping in view the cost of capital to BEML or the rate of interest provided for in the Contract Agreement or the rate of interest awarded under the Arbitral Award under challenge.

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1, Bhagirathi, Rameshwaram Colony,  
 Bariatu Road, Ranchi-834009  
 Jharkhand, India

**SPECIAL CONDITIONS**

1. The tender shall remain open for acceptance for a period of 90 days from the date on which the tenders are due to be submitted.
2. The contractor shall visit the site to acquaint himself with site conditions and study the drawings and specifications in detail prior to tendering, and no claims will be entertained later on the ground of ignorance or otherwise of the conditions under which the work shall have to be executed.
3. The contractor shall arrange for at least one qualified Engineer with experience in similar construction work to be at the work spot through out the period of construction to ensure correct undertaking and execution of the work as per drawings and specifications.
4. The setting of the building shall be done by the contractor himself, All measurements shall comply with the dimensions noted on the drawings. The contractor shall construct centre line pillars and Bench Marks wherever necessary at his own cost and the setting out shall be got checked, approved and certified by the Engineer-in-charge before execution of the work.
5. Foundations shall generally conform to the dimension indicated on the drawings, unless the nature of soil after excavation examined by the Engineer-in-charge , of works necessitates modifications. The foundation trenches for RCC columns and walls after excavation indicated on the drawing shall be got inspected, approved and certificated by the Engineer-in-charge of works before laying concrete.
6. Provision shall be made during the progress of work for embedding Electric conduits etc., wherever necessary as directed. Openings shall be left for service lines, machine foundations, as required and as per instructions of the Engineer-in-charge.
7. Care shall be taken in execution of work not to damage service lines etc., coming in the way of construction. If any damage is caused in the lines, the cost of replacing or repairs shall be borne by the contractor.
8. CONTRACTOR(S) shall provide himself/themselves with requisite number of welding sets, mixers with hoppers, vibrators builders hoist, Tools, meters and testing equipments, transport vehicles, etc., required for the complete satisfactory execution of work.
9. **WATER:**

While Company shall make all endeavors to supply water to the Contractors on a chargeable basis, the Contractors should examine the possibility of making their own arrangements for the water required for construction activities. It is suggested that the Contractors could drill required number of boreholes from where available water

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

could be used by them by pumping the same for the Construction activities. In such a case, the borewell sunk by the Contractors shall remain the property of the company. After completion of the work, the Contractors will not be charged for the water which he consumes from such bore wells.

- i) If the nature of the soil encountered with demands the use of casing pipes for the borewells, the contractor has to provide casing pipes to enable him to draw water from the borewell, and the contractor shall hand over the borewell with such casing pipes to the company for which no extra payment would be made. The contractor could however with draw the pumping sets and other accessories used by him for pumping water out of the bore wells.
- ii) Where the contractor does not draw water from company's source and makes his own arrangement for water required for the work, as certified by the Engineer-in- charge, then no recovery shall be effected from the contractor's bill.
- iii) In Case company supplies water for construction purpose, water shall be supplied at a single point as near as possible to the work spot, from which the contractor has to draw his own distribution system. The following procedure shall be followed for recovery of the cost of water so consumed by the contractor.
- iv) A meter shall be installed by the contractor at his own cost which shall be duly certified for calibration. Based on the meter readings recovery shall be affected at the prevailing rates of Bangalore Water Supply Board.
- v) In Case contractor is not able to install a meter due to various circumstances or the meter fixed mal-functions, and he continues to draw water supplied by the company, the recovery towards water shall be effected based on the quantity of water consumed which would be assessed as follows :
  - a) For Building works involving excessive use of cement like construction of buildings, Hangars, Concrete hard standing, etc., consumption of water will be calculated at the rate of 455 liters per bag of cement consumed for the work (including wastage) and this consumption shall be charged as per rates stipulated in the contract.
  - b) For such works where consumption of cement is negligible like construction of Roads, and this consumption of the water shall be at the rate of 0.5% of the value of the contract as per the final bill.
  - c) The water supplied by the company shall be used only for bonafide work as directed by Engineer-In-charge ,.

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1, Bhagirathi, Rameshwaram Colony,  
 Bariatu Road, Ranchi-834009  
 Jharkhand, India

**10. POWER SUPPLY TO THE CONTRACTORS :**

Electricity required for the work may be arranged by the contractor at his own cost. However it may be provided at a nearest point by BEML on request based on availability at the prevailing rates supplied by Jharkhand Electricity Board and the amount will be recovered from the contractors running bills. If necessary the contractor may install a separate energy meter at his own cost. However, contractor has to make his own arrangement to work during power failures/non-availability of power. Non-availability of power will not be a reason for delay in works

**11. TAXES:**

WHATEVER Taxes and duties, as applicable, chargeable in respect of this contract whether by the Central or State Government shall be borne by the contractor(s) and the price quoted shall be inclusive of such taxes, cess or any other statutory duties or taxes payable by them and price quoted shall be firm and shall be inclusive of such duties and taxes. WHEREVER Taxes are deductible at source, the company will recover the amount as per the statutory requirement.

12. THE Contractor shall agree to execute the work progressively in co-ordination with the concerned officers or shop supervisors and as directed by Engineer-in-charge..

13. THE specifications contained in the MES Schedule (referred to in the tender) in appropriate sections shall apply to this contract to the extent applicable, Cement co-efficient shall also form part of MES Schedule.

**14. VALUATION OF DEVIATIONS:**

Every deviation shall be subject to the limits specified as under:

- a. The net value of all deviations (additions and deductions) including non tendered items, of the value of work completed, shall not exceed 20% of the approved contract value and 40% in respect of any individual item, indicated in schedule A & B -BOQ
- b. In case of non tendered items, the total value of such non tendered items shall not exceed 5% of the approved contract value.

The basis for ascertaining the non tendered items shall be as follows:

- (i) The value of all deviations shall be ascertained by measurements, on the basis of the rates or prices for similar work in the bill of quantities of the same contract in so far as such rates or prices apply.
- (ii) Where the rates or prices in Bill of Quantities do not apply, the value shall be based upon rates or prices deduced there from to the extent practicable to do so.

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

- (iii) The rates for NT items shall be based on the SSR rates after proportionate adjustment in comparison with the tendered rates of like items in the contract. The basis to be adopted for working out the NT rate is the comparison of the NT item with similar trade item in the bill of Quantity for which the contractor has quoted.
- (iv) wherever NT items cannot be deduced from the like items quoted in the tender or SSR rates, market rate shall be allowed based on vouchers/invoices as per the actual including transportation, labour etc., plus 10% overheads and the labour rate shall be taken as per minimum wages in force, based on the recommendations of the Chief Engineer.
- (v) As a last resort a tender shall be floated to ascertain the rate for NT items. All Deviations in contracts for works including non-tendered items shall be approved by the Competent Authority as per DoP within the limits prescribed in the contract. The deviations and NT items shall be technically checked and processed by the respective "Engineer-in-charge " in concurrence with Finance Department of the respective division.

### 15. PROVISION OF FITTING/FIXTURES OF DIFFERENT MAKE:

The contractor shall provide the same make of fittings/fixtures specified in the tender documents unless he has quoted for other equivalent for genuine reasons. In case due to exigency of the work and difficult market conditions, the contractor is not able to provide the same make, he shall be allowed to provide equivalent approved make subject to his obtaining the concurrence of the Chief Engineer for the price adjustment as between the quotation and the purchase price for the item involved. The base for reckoning shall be the date of purchase. The contractor shall produce purchase invoice as a proof of expenditure for the items other than those specified in the tender documents allowed for incorporation in the work. Construction Department in respective Divisions/Regional/District Offices shall ensure the reasonableness of the rate in the purchase bill produced by the contractor. The price adjustment shall be the difference between the two makes on the date of purchase.

16. The Company reserves the right to accept the tender in parts i.e. on the basis of lowest quotation in each part or as a whole, at its own discretion and hence it is important that the tenders take sufficient care and quote reasonable rates in each part, so that if one part only is separated and entrusted to one Contractor he should be able to do it without difficulty. The rates quoted for similar items should be consistent. THE company also reserves the right to accept the lowest or any other tender at its discretion without assigning any reasons whatsoever.

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

**17. EXTENSION OF TIME:**

Time is the essence of the contract. The contractor is bound to complete the work within the stipulated time. The Chief Engineer has to assess the delay arising out of default of the contractor. Where the delay is due to default of the contractor, and if there is no financial loss due to such delay, the Chief Engineer can recommend for grant of extension of time by the same authority who accepted the tender/awarded the contract, subject to recording the reasons for granting such extension of time.

Where the delay is due to default of the contractor, and if there is a financial loss due to such delay, the extension of time requires the approval of Competent Authority. In the absence of Competent Authority approval, Liquidated Damages for delay in completion of the work shall become enforceable.

Where the delay is not due to default of the contractor, for example: - a) not providing clear work front to the contractor by the Company, b) Company's delay in decision making for changes relating to original work., etc necessary extension of time shall be granted with the approval of Competent Authority, as per DoP without sanctioning escalation claimed by the contractor except statutory levies.

Extension of time when granted with the approval of the Competent Authority as per Company's Delegation of Powers shall have the effect of rendering the clause 'Liquidated Damages for delay in completion work' inoperative upto the period of extension of time so granted unless otherwise specifically stated.

**18. LIQUIDATED DAMAGES FOR DELAY IN COMPLETION OF WORKS**

In case the Contractor fails to complete the works and clear the site on or before the stipulated time mentioned in the Work order he shall without prejudice to any other right or remedy of the Company in this behalf pay, as agreed Liquidated Damages and not as penalty, pay sum equal to 0.5% of the Contract sum (excluding non tendered/extra items, if any) for every week's delay subject to maximum of 10% of the total final bill value of the Contract.

Liquidated Damages shall be applicable in the following cases:

- a) where the contractor fails to complete the work within the stipulated time;
- b) where the extension of time is granted with levy of LD;
- c) Where extension of time is granted without levy of LD but the contractor has failed to complete the work within the extended period.

The amount of Liquidated Damages shall be adjusted or set off against any sum payable to the contractor under this or any other contract/s awarded by the Company.

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1, Bhagirathi, Rameshwaram Colony,  
 Bariatu Road, Ranchi-834009  
 Jharkhand, India

In case where the contract is subjected to levy of LD, the Chief Engineer shall be the authorized person to issue 'Work Completion Certificate', which shall be final and binding the Company as well as the Contractor concerned.

**19. FORE-CLOSURE OF CONTRACT:**

It shall be noted that at any time after acceptance of the tender, the Company can decide to abandon or reduce the scope of work for any reason whatsoever, the Chief Engineer shall give notice in writing to that effect to the contractor. The compensation, if any, payable for such foreclosure of work shall be discussed mutually between the Company and the contractor and settled after taking into consideration the loss suffered by the contractor on account of foreclosure of the contract. The contractor shall have no claim for any compensation whatsoever on account of any profit or advantage which he might have derived consequent to foreclosure of the whole or part of the works. The Company shall have the option to take over the contractor's materials or any part thereof, either brought to the site. The amount of compensation payable to the contractor due to foreclosure shall be decided by the authority one level above the level of the authority competent to award the contract, or by the CMD.

20. BEML revised General Conditions together with BEML specifications will form part of the contract. Should there be any discrepancy between the provision in the Bill of quantities and drawings, the former shall be deemed to take precedence there over.
21. No modification or change of specifications in the bill of quantities shall normally be accepted and such changes are to be rejected. Acceptance of such deviations shall be at the discretion of the Engineer-in-charge.

**22. EARNEST MONEY DEPOSIT:**

TENDERES should submit their tender accompanied by EMD of value indicated in the tender. It should be paid by online mode, bank draft or Bankers Cheque drawn in favour of the Company along with tenders. Tender without Earnest money deposit will be rejected. On finalization of the tender, Earnest money deposit will be refunded to unsuccessful tenderers under proper acknowledgement.

In case, the contractor/firm after quoting, withdraws from the tender or refuse/delay in commencing the work or stop the work abruptly, their EMD/ SD, as the case may be, will be forfeited. No interest amount is payable on EMD.

**23. SECURITY DEPOSIT:**

The successful tenderer shall be required to furnish security deposit for the fulfillment of contract and amount shall be 10% of the value of the contract, to be paid by the contractor. No waiver can be allowed in this regard. Such security deposit shall not entail any interest payment on refund.

The contractor shall choose any one of the following options for payment of security deposit in writing as under:

***Signature of the Contractor(s) with seal***





**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1, Bhagirathi, Rameshwaram Colony,  
 Bariatu Road, Ranchi-834009  
 Jharkhand, India

(i) The contractor shall within 30 days of acceptance of the contract deposit the difference between Earnest Money and full Security Deposit by Demand Draft/Banker's cheque drawn on any of the commercial bank made in favour of Company.

(ii) Bank guarantee from any commercial bank equivalent to the amount of security deposit valid for a period required by BEML shall also be accepted.

(iii) The above deposit shall be held by the Company as security for the satisfactory performance of the contract. All compensations or other sums or money payable by the contractor to the Company under the terms and conditions of this contract shall be deducted from this security deposit or from any other sums that shall be due, or shall become due to the contractor by the Company on any account whatsoever and in the event of the security deposit being reduced by reasons of any such deductions the contractor shall within ten days thereafter make good these deductions.

### **23.1 REFUND OF SECURITY DEPOSIT**

The above deposit, as the name itself signifies, shall be held as Security for performance of the contract. One half of the Security Deposit i.e. 50% shall be refunded to the contractor on completion of the contract based on the recommendations of the Chief Engineer in writing that the work has been physically completed in all respects.

The balance 50% of the security deposit shall be refunded to the contractor on written demand from the contractor 1 year after successful completion of work i.e. during the DEFECT LIABILITY PERIOD.

If the Security Deposit is in the form of Bank Guarantee, on completion of the contract, the BG already with BEML will be returned to the contractor. The contractor has to then submit a fresh Bank Guarantee for 50% of the security deposit value valid for a period of 1 year from the actual date of completion of the entire contract shall be deposited by the contractor.

Any refund of security deposit shall be made only with the recommendation of the Chief Engineer.

### **24. RUNNING ACCOUNT REMITTANCE: (RAR)**

During the progress of work, contractor shall submit the claims giving complete details of work done, rate and value to the Engineer-in-charge, nominated by Chief Engineer who shall certify the rate and quantity as per the MB and prepare a statement showing the description and quantity for which he recommends payment. These claims are called RAR bills and RAR payments are made once in a calendar month or more depending upon the periodicity of contract/progress of work.

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1, Bhagirathi, Rameshwaram Colony,  
 Bariatu Road, Ranchi-834009  
 Jharkhand, India

Where the RAR payment is based on the measurements recorded in the MB, the recommendation for payment shall be stage-wise co-related with the bill of quantities.

Due to technical reasons, where pro-rata payments on stage-wise progress of work is considered necessary though not specified in the contract, the Chief Engineer with the approval of competent authority, shall decide the number/type of stages correlating with the bill of quantities and submit a statement showing the stage-wise break-up of the contract value indicating work progress details including percentage of completion, cost, and remarks, if any, of the Engineer-in-charge with a copy to Accounts in the respective Division for regulating the quantity and payment. This shall form the basis for the Engineer-in-charge to prepare a bill for actual progress of work. The basis as decided above shall uniformly be adopted for regulating all RAR payments till the final bill is submitted.

However, in respect of hidden works, recording of measurements in MB shall invariably be made then and there and the MB produced to Accounts at the time of RAR payment.

Accounts shall arrange payment for RAR bills within a fortnight's time from the date of receipt based on the certification of the Engineer-in-charge and after necessary check/verification.

As per Expenditure Management Commission, Government of India, in large projects above Rs.10.0 Crore, 50% of running bill amount shall be released within 7 days of submission without a detailed check on the claim. The balance shall be released after the claim is scrutinized as per procedure in order to get more competitive bids and for speedy execution as cash flow is a critical requirement in a project.

The contractor shall also be paid 'Material Advance' for the material brought to site for incorporation in the work duly certified by the Engineer-in-charge. For such materials brought inside by the contractor, the contractor has to produce necessary test certificates from reputed Testing Laboratories for steel and hypothecation deed duly executed by the contractor in favour of the Company on a non-judicial stamp paper of requisite value.

Payment of 'Material Advance shall be recommended by the Engineer-in-charge for materials required to be used in the works as per the planned progress of work. However, payment of material advance against materials brought to site by the contractor ahead of scheduled progress of work shall be considered not exceeding 75% of the value of such material in exceptional cases with the approval of Competent Authority, with justification recorded in writing.

RAR payments shall be regulated to the extent of the value of work done, with due adjustments for recoveries and other payments (including material advance/adhoc payments made if any) effected so far against the contract.

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

**25. PRE FINAL RARs**

Pre-final RAR is raised only when the work is completed and the complete measurement is recorded in the MBs by the Engineer-in-charge designated by Chief Engineer duly accepted by the contractor.

Pre-final RAR shall be sent to the Accounts Department by the Engineer-in-charge Only after Technical check of the measurements and endorsement in the MBs by the Chief Engineer.

The Engineer-in-charge, shall recommend for payment not exceeding 90% of the value of work completed with due adjustments for recoveries and RAR payments (including Material advance if any) effected so far against the contract.

Such bills shall be paid within 2 weeks from the date of their receipt in the Finance Department after scrutiny and check for the correctness of the bill duly linking up with the MBs.

The recommendation of Pre-final RAR is based on the discretion of the Chief Engineer on case to case basis.

**26. ADHOC PAYMENTS:**

If payment for final bill could not be arranged within 5 months from the date of the completion of the contract for genuine reasons other than undue delay in submitting the final bill by the contractor, an Adhoc payment not exceeding 90% of the value of the work done after making all necessary deductions for statutory dues, RAR payments, Material advances if any paid, shall be recommended by the Chief Engineer with the approval of respective Complex chief/ respective Business Group Director. Such Adhoc payment can be recommended only if the contractor is having concurrent running contracts in the Complex.

The following guide-lines shall be adopted while making such adhoc payment;

- Such payment shall not exceed 90% of the final bill value.
- All conditions of contract and recoveries to be effected shall be taken care before effecting Adhoc payment.
- If a contractor has no other contract concurrently running in the Complex, adhoc payment need not be made. Instead, final bill shall be expedited and paid atleast within six months from the date of completion of the contract.

**27. COMPLETION CERTIFICATE:**

As soon as the Contractor completes the work assigned to him the same shall be inspected and if found satisfactory shall be taken over by the Chief Engineer. A "Completion Certificate" shall be issued to the contractor within 30 days from the date the contractor has given request for the same. If there are minor defects which can be rectified even after the building has been taken over, the defects shall be listed out and the contractor shall be asked to rectify the same before the final bill is submitted. The

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

final bill along with the completion certificate duly certified by the Engineer in charge, shall be submitted to Finance Department for payment. The completion certificate shall have the following details:

- a) Particulars of the work and Contract Number,
- b) The date of work order to commence the work,
- c) Date of completion as per original contract agreement,
- d) Actual work done value.
- e) Extension of time if any, granted,
- f) Date on which contractor was required to complete the work,
- g) Actual date of completion and taking over by BEML.

**28. FINAL BILL:**

On completion of the work, a final bill shall be submitted by the contractor. On receipt of the final bill duly signed by the contractor, the same shall be scrutinized by the Engineer-in-charge to see that the claim is in order.

The final bill prepared by the Department and accepted by the contractor, shall be accompanied with the following documents:

- Original Completion certificate
- No claim certificate duly signed by the contractor
- Original Contractor's All Risk Insurance Policy covering up to the actual date of completion of work.
- Contract Agreement
- Revised estimate as duly approved by Competent Authority, if applicable.
- Any other documents which are specified by the Management from time to time.

The Engineer-in-charge has to certify in the work Completion certificate that the work is executed in conformity with the contract specification, drawings and other conditions. The final bill duly checked and co-ordinated by the Engineer-in-charge shall be sent to the Finance Department through Chief Engineer along with the documents stated above.

**29. DEFECT LIABILITY PERIOD:**

The period of maintenance for the subject work shall be **ONE YEAR**.

During this period, the contractor shall be responsible to rectify all the defects noticed and attributable to the work done by him in respect of works executed by him. As soon as any defect in the work come to the notice, the Chief Engineer shall inform the contractor, in writing, to rectify the defect and inform him that in case he fails to do so within a reasonable time, the Company would rectify the defects at his risk and expense as per the conditions of the contract.

If the contractor does not attend to the rectifications in spite of repeated requests, the Company shall proceed at his risk and expense and get the work completed. The cost

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

incurred by the Company shall be recovered from the defaulting contractor. The Company shall forfeit the balance 50% of the Security Deposit retained and adjust this amount against the expenses so incurred. The balance amount, if any, after recovering the expenses incurred shall be refunded to the contractor. In case the amount available is insufficient to cover the expenses in full, that portion of the expenditure still remaining unadjusted shall be recovered from any of the subsequent bills due for payment to the contractor against any other contract.

Even after such adjustments, the amount available is insufficient to cover the expenses in full, the Company reserves the right to take legal course of action to recover such unadjusted amount.

### 30. **CONTRACTORS LIABILITY AND INSURANCE:**

From commencement to completion of the works, the contractor shall take full responsibility taking precautions to prevent loss or damage. He shall be liable for any damage or loss that shall happen to the works or any part thereof.

In addition, the contractor shall indemnify and keep the Company indemnified against all losses and claims for injuries or damages to any person or any property whatsoever which shall arise out of or in consequence of the construction works. For this purpose, the contractor shall take an insurance policy- "**Contractors All Risks Insurance**"- to cover the risks, as per the Conditions of the Contract. The insurance policy has to be kept valid till the work is completed and the possession handed over to the Company. The policy shall be taken at his cost showing the Company as the 'principal' to simplify the work in the matter of raising claims and settlement thereof.

31. MATERIALS obtained from demolition/dismantling work shall remain with the Contractor at his own risk till such time the Contractor removes them to BEML stores or as directed within 10 days from the date of completion. If he fails to remove such dismantled materials to BEML stores or as directed within 10 days from the date of completion, the Engineer-in-charge will be entitled to remove them at the risk and cost of the Contractor.
32. THE various provisions in this special condition shall be deemed to take precedence over those in General conditions/specifications to the extent applicable.
33. The quoted rate is deemed to include for execution of work in a phased manner/part by part if necessary and as directed by BEML and no extension of time nor extra claims shall be entertained in the regard.

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

### CEMENT CO-EFFICIENT SCHEDULE:

Sl. No.	Description	Unit	Cement in Kgs
01.	CC 1:1.5:3 Types A1 & A2	CM	403.50
02.	CC 1:2:4 Types B1 & B2	CM	320.80
03.	CC 1:3:6 Types C1 & C2	CM	216.20
04.	CC 1:4:8 Types A1 & A2	CM	170.00
05.	CC 1:5:10 Types DE2	CM	129.20
06.	Brick work in ( one brick) CM 1:6	CM	49.34
07.	Brick work in ( ½ brick) CM 1: 4	CM	63.51
08.	Damp proof course in CM (1:2) 10mm thick	SM	7.19
09.	Damp proof course in CM (1:2) 15mm thick	SM	10.81
10.	Walling of random or polygonal rubble in gauged mortar 1:1:6	CM	89.69
11.	Size stone in gauged mortar 1:1:6	CM	62.79
12.	Walling of random or polygonal rubble in CM 1:4	CM	143.50
13.	Size stone masonry in CM 1:4 in foundation	CM	89.69
14.	Size stone in CM 1:4 in basement and superstructure with joints neatly dressed.	CM	80.72
15.	Size stone masonry in CM 1:6 in foundation	CM	62.79
16.	Size stone masonry in CM 1:6 in superstructure.	CM	56.66
17.	Size stone masonry in CM 1:8 in foundation	CM	51.13
18.	Rendering or screeding 10mm thick in brick/concrete in CM 1:2	SM	7.80
19.	Rendering or screeding 10mm thick in brick/concrete in CM 1:3	SM	6.24
20.	Rendering or screeding 10mm thick in brick/concrete in CM 1:4	SM	5.04
21.	Rendering or screeding 10mm thick in brick/concrete in CM 1:6	SM	2.58

**Signature of the Contractor(s) with seal**



**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1, Bhagirathi, Rameshwaram Colony,  
 Bariatu Road, Ranchi-834009  
 Jharkhand, India

22	Rendering or screeding 10mm thick stone masonry in CM 1:2	SM	9.08
23	Rendering or screeding 10mm thick stone masonry in CM 1:3	SM	7.28
24	Rendering or screeding 10mm thick stone masonry in CM 1:4	SM	5.90
25	Rendering or screeding 10mm thick stone masonry in CM 1:6	SM	4.42
26	Pointing to block squared rubble coursed or un coursed in CM 1:2	SM	3.88
27	Pointing to block squared rubble coursed or un coursed in CM 1:3	SM	2.95
28	Pointing to block squared rubble coursed or un coursed in CM 1:4	SM	2.46
29	Pointing to block random rubble in CM 1:2	SM	4.87
30	Pointing to block random rubble in CM 1:3	SM	3.66
31	Pointing to block random rubble in CM 1:4	SM	3.06

**Signature of the Contractor(s) with seal**



**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1, Bhagirathi, Rameshwaram Colony,  
 Bariatu Road, Ranchi-834009  
 Jharkhand, India

**PARTICULAR SPECIFICATIONS**

**1. GENERAL:**

These particular Specifications are to be read in conjunction with the specifications contained in the MES Standard Schedule of Rates 2010, i.e. PART I - Specifications and PART II-Rates, including errata (here-in-after referred to as the MES Schedule) and specifications given hereunder and the drawings mentioned in these documents, rates and specifications thereon shall be deemed to apply to the works unless mentioned otherwise in the tender documents. In case of discrepancy between the documents, viz., Bill of Quantities, Particular specifications and Drawings, the following order of precedence shall be followed:

- (a) Bill of Quantities
- (b) Particular specifications
- (c) Drawings

**2. SCOPE OF THE CONTRACT:**

THE contract comprises full, final and entire completion of Subject Work all as shown in Schedule-A & B and as described in these Particular Specifications and detailed in the drawings given in the list of drawings enclosed hereto and also subject to the General and Special Conditions of Contract. The work shall be completed in stipulated period.

THE time for completion is to be reckoned from the date of commencement mentioned in the Work Order.

**3. SAMPLES OF MATERIALS:**

THE contractor shall produce samples of all materials and shall obtain approval of Engineer-in-Charge in writing before he places bulk order for the material for incorporation in the works. In respect of materials for which samples are not kept or detailed specifications are not given herein-after, such materials shall comply with the latest relevant Indian Standard Specifications as published upto the date of issue of this tender.

- 3.1. THE contractor shall on demand produce original receipted vouchers / invoices in respect of materials supplied by him.

**4. PROPRIETARY MATERIALS:**

THE contractor shall ensure that proprietary materials like paints etc., are brought to site in original sealed containers / packing and bear the manufacturer's markings.

**5. CLEANING DOWN:**

THE contractor shall clean all the floors, walls, glass panes, fittings and fixtures, etc., touch up all painter's works and carryout all other necessary items of work in

***Signature of the Contractor(s) with seal***





**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1, Bhagirathi, Rameshwaram Colony,  
 Bariatu Road, Ranchi-834009  
 Jharkhand, India

connection therewith and leave the whole premises clean and tidy before handing over the buildings.

**6. ATTENDANCE UPON BUILDING:**

THE contractor shall permit free access and generally afford facilities and usual convenience to other agencies and or departmental workmen to carryout works under separate arrangements.

THEREFORE, the rates quoted by the contractor shall be deemed to include for all such costs as consequence for having to work in the circumstances described above and no claim shall in any event be entertained on this account.

**7. EXCAVATION AND EARTH WORK:**

THE earthwork, excavation, filling etc., in ordinary/hard soil shall be carried out to the extent ordered/indicated in the drawings. Excavation inadvertently made deeper than what is ordered or indicated in the drawings shall be made good by the contractor with PCC 1:4:8 using not larger than 40mm graded granite aggregate with out extra cost to the company.

The earth obtained from excavation shall be filled, spread, watered and well rammed in layers not exc. 20 cm thick around foundations, under floors and in other situations to make up levels / slopes as directed/shown in drawings. Use of vegetable soil, turf, peat and black cotton soil in filling shall not be permitted. No lead whatsoever shall be allowed extra for earth obtained from excavation and reused for filing around foundation and under floors. If on the actual excavation, hard rock or ordinary rock is met with the contractor shall intimate the Engineer-in-charge in writing for making necessary price adjustment. Excavation done in ordinary/hard rock will be priced as an authorized extra item.

**8. CONCRETE MATERIALS**

8.1 **CEMENT:** Cement used in the work shall be ordinary PORTLAND/PUZZOLANA cement and shall be stored by the contractor in a dry place under proper cover and stack. Stacks shall not be more than 10 bags high.

8.2 **FINE AGGREGATE:** Fine aggregate (sand) for concrete shall be of approved quality natural sand. Fine aggregate shall be clean, free from any admixture of clay, loam, silt, organic matter and other impurities.

8.3 **COARSE AGGREGATE:** Coarse aggregate for concrete shall be of approved broken granite stone and shall conform to IS-383-1963.

8.4 **WATER:** Water used in concrete shall be clean, fresh and non-saline.

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

Rate: Rate quoted for cement concrete works in Schedule-A & B shall include the cost for the use and waste of formwork as necessary.

Unless otherwise specified, the rates quoted against various items of schedule 'A' & 'B' shall not include for plastering. The various concrete surfaces shall be finished as under:

- a) All concrete surfaces occurring in conjunction with wall and the like: Immediately after the formwork is removed all irregularities shall be removed and air holes shall be stopped with CM 1:3 so that the surface is ready for application of plaster which is paid for separately.
- b) Soffits & edges of roofs, soffits & edges of chajjas, facias, soffits and sides of beams and columns, exposed surfaces of shelves, not occurring with conjunction of walls: These shall be finished as described above to receive plastering which is paid for separately.
- c) Exposed surfaces of concrete members other than those specified above and tops and edges of chajjas and the like, independent columns and other concrete surfaces not specified to be plastered: These surfaces shall be finished fair and smooth. On account of any reason whatsoever, if fair and smooth surface cannot be achieved, the contractor is permitted to plaster these surfaces with CM 1:3, to obtain a fair, uniform and smooth finish. However, he shall ensure that the thickness of plaster is kept to a minimum. The contractor shall not be paid anything extra for the application of this CM 1:3 plaster.
- d) The rate quoted for pre-cast concrete shall include for cost involved in the cutting of grooves, etc., in walls, etc, and fixing as specified.

### 8.5 **Mixing concrete:**

All concrete shall be mixed in mechanical concrete mixers with hopper. The mixing drum shall be washed and cleaned on completion of work, every day and on every stoppage of work, if the stoppage exceeds 30 minutes. If the total quantity of concreting proposed to be carried out in any one day does not exceed 0.25 cum hand mixing may be adopted for such concrete.

## 9. **FORM WORK**

All form work shall be as mentioned in MES schedule 2009, Part I, section 7, Where concrete is to be finished smooth, the forms shall be wrought on the inside surface. Contractor may at his discretion use steel or plywood form work in lieu of timber formwork at no extra cost to the Company.

## 10. **COMPACTING CONCRETE**

The compacting of concrete shall be done all as specified in SSR Part I – Specifications. The mechanical vibrator shall be used to compact the concrete in

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

footing, columns and beams etc., and vibrator shall be used to compact the PCC 1:2:4 in flooring and shop irrespective of the fact whether the thickness of concrete exceeds 30 cm or not.

### 11. CONCRETE CUBES AND TESTING

Test cubes shall be taken from the important concrete works for testing purpose at the sole discretion of the Engineer-in-charge. Such tests shall be performed at the expense of the contractor.

### 12. HOLLOW CONCRETE BLOCKS:

Hollow Concrete blocks shall conform to the requirements of IS-2185 specifications for hollow concrete blocks. Hollow blocks shall be sound, free from cracks, broken edges, honey combing and other defects that would interfere with the proper placing of blocks or impair the strength or performance of construction. The water absorption shall not exceed 240 kg./Cum.

**TOLERANCE:** The maximum variation in the dimensions shall be not more than +/- 1.5mm for height and breadth and +/- 3.0mm for length.

The total width of cavity in any block measured horizontally at right angles to the face of the block as laid in the wall, shall not exceed 65% of the total breadth (that is the overall dimensions of the block at right angle to the face of the block as laid in wall) of the block. The volume of the cavity in the block shall not exceed 50% of the gross volume of the block.

Surface characteristics of blocks intended to be plastered or rendered, shall be such as to provide a satisfactory bond with the plaster.

Faces of blocks shall be flat and rectangular, opposite faces shall be parallel and all arises shall be square. The ends of the blocks which form the vertical joints may be plain butt unless tongue and grooved or double grooved ends are indicated.

The block shall be cured in an immersion tank or in a curing yard and shall be kept continuously moist for atleast 21 days. When the blocks are cured in an immersion tank, the water of the tank shall be changed atleast every four days.

After curing, the blocks shall be dried in shade before being used on the work. They shall be stacked with voids horizontal to facilitate through passage of air. The blocks shall be allowed to complete their initial shrinkage before they are laid in the wall.

### **Construction of Masonry:**

For single storeyed buildings, the hollows of blocks in the foundation and basement masonry shall be filled up with sand and only the top foundation course shall be of solid blocks. But for two or more storeyed buildings solid concrete blocks shall be used in foundation courses, plinth and basement walls unless otherwise indicated. The

***Signature of the Contractor(s) with seal***



## **BEML LIMITED**

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

hollow blocks are used, their hollows shall be filled up with cement concrete 1:3:6 using 12.5 mm nominal size aggregate.

### **Wetting of Blocks:**

Blocks need not be wetted before or during laying in the walls. In case of the climatic condition so required, the top and the sides of the blocks may only be slightly moistened so as to prevent absorption of water from the mortar and ensure the development of the required bond with the mortar.

### **Laying:**

Blocks shall be laid in mortar, as indicated and the roughly bedded in mortar, spread over the entire top surface of the previous course of blocks to a uniform layer of not less than 10mm in thickness and not more than 12mm.

All courses shall be laid truly horizontal and all vertical joints made truly vertical. Blocks shall break joints with those above and below for not less than quarter of their length pre-cast half length closers (and not cut from full size blocks) shall be used for battered faces; bedding shall be at right angles to the face unless other-wise directed. Care shall be taken during construction to see that edges of blocks are not damaged.

### **INTERSECTING WALLS:**

When two walls meet or intersect and courses are to be held up at the same time, a true masonry bond between atleast 50 percent of the units at the intersection is necessary. When such intersecting walls are laid up separately pockets with 20mm maximum vertical spacing shall be left in the 1<sup>st</sup> wall laid. The corresponding course of the 2<sup>nd</sup> wall shall be built into these pockets.

Fixtures, fittings, etc., shall be built into the masonry in cement and sand mortar 1:3 while laying the blocks where possible. Hold-fasts shall be built into the joints of masonry during laying.

Holes, chases, sleeves, openings, etc., of the required size and shape shall be formed in the masonry with special blocks while laying, for fixing in pipes, service lines, passage of water, etc. After service lines, pipes, etc., are fixed voids left, if any, shall be filled up with cement concrete 1:3:6 type and neatly finished. Construction details specified for block masonry which have not been specified herein shall apply to hollow blocks masonry to the extent applicable.

### **FINISHES:**

Renderings shall not be applied to the walls when these are wet. Joints for plastering or pointing, as specified shall be raked to a depth of 12mm. Joints on internal faces, unless otherwise indicated shall be raked for plastering.

***Signature of the Contractor(s) with seal***



**BEML LIMITED**  
 (A Government of India Undertaking)  
 206/D1, Bhagirathi, Rameshwaram Colony,  
 Bariatu Road, Ranchi-834009  
 Jharkhand, India

**13. SIZE STONE MASONRY IN CEMENT MORTAR IN FOUNDATIONS**

Face work shall be hammer dressed with no stone to tail into a point. No face stone to be narrower or shorter than its height. Thickness of mortar in beds and joints shall not exceed 20mm. HEIGHT OF COURSES 150mm to 230mm but no course shall be greater in height than any course below.

- 13.1 **BOND OR THROUGH STONES:** Bond or through stones shall be provided at 1.5m in every course and are to be staggered. No stone shall tail into a point. Bond stones shall extend from the front to the back of walls. For walls 600mm thick and under, bond stones shall be in one piece. For walls over 600mm thick they shall either be in one piece (if available locally) or be in series of headers, each header overlapping the adjoining one by not less than 150mm. No header shall preferable be less than 600mm in length.
- 13.2 Quoins and jambs to be squared back in beds and joints are faced as ordered.
- 13.3 **HEARTING** Stone to be not less than 150mm in any direction, carefully laid hammered down into place with wooden mallet and solidly bedded with mortar. The hearting must not be brought to same level as the facing stones with spalls or pinning, which are only to be used as wedges in the hearting.

**14. SIZE STONE MASONRY IN PLINTH AND SUPER STRUCTURE**

Facing stone shall have hammer dressed faces with no stone tailing into a point. No face stone shall be narrower or shorter than its height. Face beds shall be squared back at least 50mm and joints 25mm. No spalls or pinning shall show on face. All other details shall be as detailed herein before for foundations.

**15. BRICK MASONRY IN CEMENT MORTAR**

Brick shall be table moulded / clamp burnt bricks locally available of approved quality having a minimum compressive strength of 50kgs/Sq.cm from the local kilns and shall be used in bonds as specified in MES schedule 2009 Part I, Section – 5.

**16. WOOD WORK JOINERY**

- 16.1 **TIMBER:** Unless otherwise specified the timber used in all situations shall be of good quality of wood as detailed in relevant items of schedule 'A' & 'B'. The timber shall be well kiln seasoned and free from defects of any sort. The contractor should particularly note that all timber required for the work should be brought to site, cut to required sizes and properly stacked and stores well ahead of actual use as directed by the Engineer-in-charge.
- 16.2 **FINISH:** Unless otherwise specified timber surfaces shall be wrought and sand papered smooth. However, backs of chowkats can be left clean saw and shall be tarred and sanded before erecting in position.

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

- 16.3 TOLERANCE: Tolerance for wrought faces of joinery is as specified in MES schedule SSR Part I, Section 7, except in the case of practical board panel shutter/boarding/planking wooden beads which shall hold the full thickness/sizes shown in drawings. The overall dimensions of door etc., as shown in drawing shall be maintained.
- 16.4 PLUGGING: Wooden plugs for fixing timber fixtures and fittings and the like in walling or concrete shall be cut to size, tapered and built into walls. 'PHIL' plugs made out of asbestos cement powder where specified in the drawings or as directed shall be used wherever raw plugs are specified in the drawings or as directed the same shall be fixed after punching holes of the correct size.
- 16.5 JOINERY: Provide timber doors and other joinery all as per details shown in drawings and as specified in schedule 'A' & 'B'. All door shutters shall be fixed so that there is a clearance of 3mm between the finished floor level and the bottom edge of shutter. The chowkats size is as shown in the drawings/described in Schedule 'A' & 'B'.
- 16.6 Nails and spikes shall not be used in joinery works. Bamboo wood pins of proper sizes only shall be used. All joiner's works chowkats shall be cut and framed together soon after commencement of building operations, but shall not be wedged up until required and passed. Any portion that may warp or develop shakes or other defects shall be replaced with new ones before being placed in position. Timber chowkats shall be fixed in position all as directed and shown on drawings.
- 16.7 Paneled and battened doors/flush shutters/glazed doors : Styles and rails of skeleton frames for shutters shall be out of well kiln seasoned timber of the species specified in Schedule 'A' & 'B' and panels shall be as specified in Schedule 'A' & 'B'. The flush shutters shall be having solid core type with well seasoned block board and commercial veneered face and approved by the Engineer -in-charge. All flush shutters shall be provided with internal lipping to a total depth of 25mm. The width of lapping shall be equal to the thickness of core.

### 17. STEEL WINDOWS / VENTILATORS:

- 17.1 Steel windows / ventilators shall conform to IS-1038 / IS-1361 and of approved make. The fittings such as handles etc., shall be as specified and in Schedule- A & B & shall be fixed as per manufacturers instructions.
- 17.2 For steel windows, steel hold fasts of size shown in drawings and fabricated all as per "DETAILS of lugs for brick or concrete" shown in the leaflet of manufacturer shall be provided. The number of hold fasts/lugs shall be as indicated in the above leaflets.
- 17.3 Glass panes using standard anodized aluminium beads fixed with chromium plated flat head steel screws or as specified in schedule 'A' & 'B'. Glazing to windows shall be of selected quality as specified in schedule-A. MS guard

**Signature of the Contractor(s) with seal**



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

bars/weld mesh to the windows, wherever indicated shall be provided as specified and shown in drawings.

### 18. STEEL AND IRON WORK

Steel and iron work shall be executed all as indicated in the drawings and as per standard practice in the best workmanship like manner and shall conform to IS-1786 and IS-226.

- 18.1 The rate quoted by the contractor against structural steel items of Schedule 'A' & 'B' shall be applicable for various steel sections required and used for the work. Bolts and nuts required for the work shall be procured by the contractor.
- 18.2 The preamble under structural steel work of SSR Part I and other relevant notes and specification of SSR shall apply to this work. One coat of red oxide shall be coated to the structural steel surfaces before erection and two coats of approved enamel paint shall be done after fabrication and hoisting on all exposed surfaces and before fixing the sheets. No deductions shall however be made for the two coats of painting in respect of structural steel surfaces of columns, trusses, etc., which are embedded in brick or stone or concrete after erection and fixing in position is complete.
- 18.3 STEEL bars incorporated in the reinforcement concrete work shall be all as per details shown on the drawings.
- 18.4 LAPS and crossings shall be tied with mild steel wire annealed of size not less than 0.9mm conforming to IS 280, to be procured by the contractor.
- 18.5 Welding of bars shall be done where indicated or directed by Engineer in charge in lieu of lapping in accordance with IS-2751. Welding in general shall be done as described for structural work. Bars upto and including 20mm shall be lap welded and those larger than 20mm dia shall be butt welded. IN case of lap welds, the length of lap shall be five times the dia or 100mm whichever is greater. The throat thickness shall not be less than 3m for bars upto 16mm dia and 5mm for bar over 16mm dia and upto 20mm dia.
- 18.6 All structural steel shall be fabricated and fixed at site as and where shown in the drawings. Welding should be of arc welding and shall conform to IS-823-1692. Electrodes used for welding should conform to IS-814-1963. Welding design and welded fabrication of standard steel shall conform to IS-816-1956 and IS-800-1962 respectively.
- 18.7 The contractor shall be responsible for accurate fixing of reinforcement shown in drawings and shall not place any concrete until the reinforcement has been inspected in position, and passed (one day prior to concreting) by the Engineer -in-charge ,. The contractor shall take necessary precautions to prevent any displacement of reinforcement bars during concreting.

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

- 18.8 The weight of all types of steel/bars shall be calculated from the weight conversion given in the relevant ISI tables and the sections for which conversion is not available in the ISI tables; the actual weight conversion of such sections shall be arrived at for the same. The alignment shall be made carefully to suit the operation of EOT cranes all as directed by the Engineer in charge.

Flat/sloped RCC roof shall be provided all as shown on drawings and as specified and directed complete.

### 19. WATER PROOF COURSE

Water proof course with lime concrete and machine made pressed clay tiles: The roof surface shall be wire brushed and cleaned of all dust and foreign matter before laying the coba. Lime and brick aggregate coba shall be made out of good quality fat lime and brick aggregate 20mm size mixed in preparation of 1:3 by volume and allowed to cure for 3 days. The cubed brick bat coba shall be spread over the roof slab to the required thickness and slopes etc. and consolidated with wooden mallets using beal fruits and gur all as specified of section 11 of SSR Part I, and finished rough. Over the coba, one course of machine made tiles or other equivalent and approved make shall be laid all as specified in Bill of Quantities.

### 20. AC RAIN WATER PIPES

Rain water pipes and accessories shall be as manufactured by approved make. The rain water pipe and the accessories shall be fixed in position as per the code of Practice published by M/s. Asbestos Cement Pvt. Ltd., and as directed. The rate quoted includes cost of accessories like bends, shoes, painted MS clamps etc., and fixing. The centre line length of the accessories shall be added to the length of pipes for purpose of measurements. The rain water pipes shall conform to IS-1626-1960.

#### Unplasticised PVC rain water pipes

Unplasticised PVC pipes shall conform to IS-4985. The pipes shall be reasonably sound. Internal and external surfaces of the pipes shall be smooth and clean, and free from other defects. Pipes shall be of pressure ratings as indicated in Schedule-A & B- Bill of quantities.

### 21. FLOORING

Floors shall be provided all as shown in drawings and as detailed in Schedule-A & B. Floors shall be laid to level and/or to slopes as shown in drawings or as directed. Slopes shall be achieved by giving required slope to earth filling under floors. Floors shall be sunk wherever shown in drawings. Floors shall be carried through all doors and other openings. Exposed edges of floors shall be finished in the same manner as for the top surface.

- 21.1 Concrete floors: Sub-floors with PCC 1:4:8 PCC 1:4:8 sub-floor shall be laid over well consolidated sub-base. The surface shall be left rough to receive the

***Signature of the Contractor(s) with seal***





## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

screeding/floor finish. Concrete floors shall be laid as and where indicated in drawings/as directed.

- 21.2 PCC floors/ramps: PCC 1:2:4 shall be laid over in alternative bays system all as described in MES schedule 2009, part I, Section 13. The top surface shall be finished as specified in schedule 'A' & 'B'.
- 21.3 Vacuum Concrete the concrete flooring with vacuum treatment to be done by M/s. Authorized firms, or other equivalent reputed agency. The concrete should be designed for medium workability and should not be dry. Surface vibrators should be used after laying the concrete. If necessary, poker vibrators should precede surface vibrators. The top layer must be leveled with surface vibrators and then vacuum processing should start after placing top cover and filter pads. Cleaning with skim floater using planning disc should be done immediately after vacuum processing. Blade polishing should be done after the concrete has hardened sufficiently.
- 21.4 Flooring/Skirting with Terrazo tiles Terrazo tiles for floor shall conform to IS-1237-1959 and shall be laid over cement mortar, screed, etc., all as specified and detailed in Schedule 'A' & 'B'.
- 21.5 Glazed Tiles Glazed tiles shall conform to relevant IS and shall be laid all as per SSR Part I and all as specified/detailed in Schedule 'A' & 'B'.

### 22. PLINTH PROTECTION

Plinth protection 75mm thick shall be provided. Plinth protection need not be provided where portions are covered by steps and ramps and shall be laid to slope as directed and in bays of length not exc. 3M adopting alternate bay system. The top surface shall be finished smooth using extra cement.

### 23. PLASTERING GENERAL

The surface to be plastered shall be prepared by raking out joints and wetting the surface thoroughly. Curing of plastering work shall be properly done by means of stirrup pumps or similar devices. The contractor shall take every precaution right from the commencement of plaster work to prevent any defect that may appear on the surface of plaster and shall be responsible to make good any portion of plaster, which in the opinion of the Engineer -in-charge requires removal and re-doing.

- 23.1 Sand for plastering and pointing work shall be as specified herein before for RCC works.
- 23.2 The thickness specified in relevant Schedule 'A' & 'B' item is the thickness above the proudest part of brick/concrete/stone surface and is exclusive of dubbing coat. Any dubbing coat that may be necessary to bring the surface to uniform level shall be provided by contractor and shall be of the same mix

***Signature of the Contractor(s) with seal***



## **BEML LIMITED**

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

specified for the plastering. The rate quoted for Schedule 'A' & 'B' items shall be deemed to be inclusive for the dubbing coat also.

- 23.3 No rounding off of external and internal angles or corners of plaster shall be done. The junction/arises shall be made true and square.
- 23.4 Plastering on walls, dados and skirting shall be returned along with the jambs of opening in walls and cills of windows.
- 23.5 Plastered surfaces shall be finished fair and even.
- 23.6 Cement Mortar Plastering: Plain cement plaster or ordinary cement plaster where shown in drawings/schedule of finishes shall be of mix/proportion and thickness as specified in Schedule 'A' & 'B' finished fair and even without using extra cement.
- 23.7 Keyed pointing: Keyed pointing to size stone masonry shall be in CM 1:4 all as MES SSR, part I.
- 23.8 Rough cast plastering : Provide rough cast plastering of thickness over and including cement mortar screeding as specified in Schedule A & B. The mixing laying of rough cast plastering shall be as specified in SSR Part I 2009.
- 24. WHITE COLOUR WASH**
- Before application of white wash/colour wash etc., the surface shall be prepared, to a clean and fair surface.
- 24.1 White wash: White wash shall be carried out to surface as indicated in drawings/schedule of finishes and all as directed by the Engineer -in-charge. White wash shall be carried out in three coats.
- 24.2 Distemper: Provide two coats of approved oil bound washable distemper over a coat of primer (cement primer) all as specified in Schedule 'A' & 'B'. Shade/tint shall be as directed by the Engineer -in-charge. The surface to be distempered shall be prepared with a coat of full putty.
- 24.3 Cement based paint: Two coats of cement based paint such as Snowcem or Surfacedem or other equivalent and approved make & colour, shall be applied on surfaces all as directed and as per manufacturer's instructions.
- 25. BUILDER'S HARDWARE**

Builder's hardware of sizes shall be provided and fixed as specified in Bill of Quantities and detailed in drawings. Sample of fittings shall be first got approved by the Engineer -in-charge before placing bulk orders for the same.

***Signature of the Contractor(s) with seal***



## **BEML LIMITED**

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

25.1 Butt hinges for doors shall be MS cold rolled steel butt hinges all as specified in Bill of Quantities and as shown on drawings.

### **26. GLAZING:**

Unless otherwise specified, glazing for doors, windows, ventilators etc., shall be with not less than 3mm thick plain glass and of the best quality. The glass shall be free from bubbles, scratches and other imperfections. The glass shall not be wavy.

### **27. PAINTING**

Paint shall comply with the relevant IS and shall be of approved manufacture. Paints for priming coat, under coat and finishing coat shall be of the same manufacture. The colour and the manufacture shall be approved by Engineer-in-charge.

27.1 Painting to steel surfaces with Enamel paint: Where painting to steel surface with enamel paint is indicated drawings/schedule of finishes, the surface shall be prepared, cleaned with sand paper to remove scales and rust. Apply a coat red oxide primer followed by two coats of synthetic enamel paint of approved make, and finish the surface so as to have a highly glossy appearance. Tints/shade of paint shall be superior tint and shall be approved by Engineer-in-charge. The tint for under and finishing coat shall be same.

Painting to Timber surfaces: Where painting to timber surfaces with approved synthetic enamel paint is indicated in drawings/schedule 'A' & 'B' the surface shall be prepared and given a priming coat using approved primer. The surface shall then be bodied in with liquid wood filler of approved make, allowed to dry and rubbed with sand paper, after moistening the surface with water. Clean the surface and then apply two coats of paint of approved quality. Tint/shade of paint shall be superior tint and shall be approved by Engineer-in-charge. The tint for under and finishing coat shall be the same.

27.2 Unless otherwise specified, the rate quoted for relevant items of Schedule 'A' & 'B' such as doors, windows, etc, shall include for two coats of painting (one under coat and one finishing coat) over a coat of primer all as specified hereinbefore.

### **28. SOLING**

The stone for soling shall be hard granite sound and free from decay. Stones shall be clean and of height equal to the thickness of soling and as described in MES schedule SSR, Part-I, Stones shall not be laid flat on the sub-grade. The soling stones shall be hand packed to the proper width and to the profile as directed and by laying correct to the template placed 5M apart, soling stones shall be laid resting on their broad bases with their height equal to the thickness of soling & the largest dimensions at right angles to the centre line. Stones shall be laid breaking joints in close contact with each other not leaning against each other. Larger size stones shall be arranged at the edges and centre. All interstices between stones shall be wedged on by smaller size stones of suitable size, well driven by crowbars, hammers to ensure tight packing. After hand packing and checking of high and low spots by templates is complete the soling shall be consolidated by power roller of 10 tones weight all as specified in Part-

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

I, section-20 of MES schedule A, covering up the surface during rolling by blinding with stone spalls and gravel, high and low spots being corrected by removing or adding the soling respectively as the case may be. Over the consolidated soling, moorum shall be spread to a thickness of 50mm, to proper levels, watered and rolled all as specified in Bill of Quantities.

### 29. WATER BOUND MACADAM

Water bound macadam shall be provided with granite stone aggregate conforming to the grading given in the table, for granite or trap of SSR Part I, under section 20, SSR part-I. The rolling shall be done with 8/10 tonne power roller. Over the consolidated surface, moorum shall be spread to a thickness of 25mm to proper level, watered and well rolled/consolidated all as per Bill of Quantities and as directed.

### 30. FERRO CEMENT WATER TANKS : MATERIALS : CEMENT :

- 30.1 Ordinary Portland cement shall be in accordance with IS-269-1976
- 30.2 Fine aggregate: Aggregate shall generally conform to IS-383-197
- 30.3 Reinforcement: Shall be in accordance with following specification
- a) Weld Mesh – IS 412 or 1962
  - b) Chicken Mesh IS 1566 of 1967
  - c) 6mm MS Rods IS 432-1966, Part I
- 30.4 Fabrication: A weld mesh and mild steel rod cage shall be cut and bent and covered either side using chicken mesh/square woven mesh all as shown in drawings. Both meshes and main mild steel rods shall be tied together using binding wire along with fittings such as drain off pipe, inlet pipe outlet pipes, over flow pipe connections and fittings hooks in correct position.
- 30.5 Casting Platform: Tank will be cast on leveled masonry platform and before casting it shall be lubricated in advance by mould oil.
- 30.6 Mixing and casting: Cement and fine river sand shall be mixed dry in proportion 1:2 by weight. Water cement ratio shall be 0.5 for preparing the wet mortar. Bottom slab shall be cast first then vertical walls can be plastered with cement mortar. Small pieces of plywood shall be used on opposite side as a back up and mortar shall be forced into cage from outside and finished to required thickness by following the same process from either side. Both inside and outside surfaces should be finished fine after initial setting of mortar. Cover shall be casted separately and finished fine.

**Signature of the Contractor(s) with seal**



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

- 30.7 Curing: The tank shall be cured by gunny bags after 24 hours of casting for 7 days. The water shall be slowly filled and leakages observed shall be made good.
- 30.8 Painting: The tank shall be painted by using tar mastic paint IS-158/8 grade by giving one coat internally after positioning the tank, 2 coats of snowcem of approved colour shall be given for external surface.
- 30.9 Testing: The contractor shall fill the tank initially in three days after painting and ensure that water level shall not fall 3mm in the 24 hours.

### 31. ROLLING SHUTTERS

Rolling shutters shall be of standard or other equal and approved make and shall be provided all as specified SSR 2009 part I. The rolling shutters shall be painted with two coats of paint over one shop coat of red oxide primer as described in Schedule 'A'.

### 32 ALUMINIUM DOORS

Aluminium doors shall be fabricated and fixed in position all as shown in drawings and as described in Schedule 'A' & 'B'. The rates quoted is deemed to include the cost of fixtures, locking arrangements etc., all as shown in drawings/directed.

SLIDING DOOR WITH TRACK: Providing sliding doors with track and other joinery all as per details shown in drawings and as specified in Schedule 'A' & 'B'. All categories of steel required for the work shall be of contractors supply. Other conditions as given in Clause 'STEEL AND IRON WORK' shall be applicable in this case also.

- 32.1 MS Sheet gutters: MS sheet gutters shall be fabricated and fixed in position including all the necessary accessories in accordance with the relevant IS and as directed by the Engineer -in-charge. MS sheets required for the work shall be arranged by the contractor.

### 33. WATER SUPPLY

Water supply (General) Work shall be carried out by licensed plumber and layout of the pipes shall be as directed by the Engineer -in-charge. All pipes shall be truly vertical/horizontal and bending of pipe shall not be permitted. Appropriate specials shall be invariably used at bends, junctions and connections.

- 33.1 Materials: Water tubing with all accessories shall be of mild steel tubes, galvanized, screwed, medium quality or light quality (conforming to IS1239) as specified in Schedule 'A' & 'B'. Stop cocks shall be screw down, high pressure pattern, heavy quality and shall conform to IS 731, stop cocks shall be of brass. Bib cocks, shall be of brass chromium plated suitable for high pressure, conforming to IS-1795-1961.

**Signature of the Contractor(s) with seal**



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

- 33.2 Laying and Fixing of pipes :Pipes running on walls/floors/roofs inside the building shall be fixed on surface of walls/roofs all as specified in Section-18, of MES 2004, Part I. However, where pipes are shown through the floors the same shall be laid in position before laying the concrete floors. Where pipes are laid underground, trenches, shall be excavated as and where directed.
- 33.3 In jointing the pipes, the inside of the socket and the screwed end of the pipes shall be smeared with red lead and few turns and hemp yard wrapped round the screwed end of the pipe, which shall then be screwed in the socket with a pipe wrench.
- 33.4 Making Good: Unless otherwise specified all holes cut in floors/walls, chases cut in walls, etc., for providing pipes etc., shall be made good by the contractor in the same manner and mix as specified for that portion of wall and or floor. Cutting in to wall or floors shall be restricted to the bare minimum extent practicable for the finished sizes of holes required. The cost involved in these items are deemed to be included in the contractors quoted rates of respective items of Schedule 'A' & 'B'.
- 34. MIRRORS**  
Mirrors shall be as per the BOQ.
- 35. SANITARY WORKS:**
- 35.1 European type water closet: Provide and fix white European type water closet all as specified in Schedule 'A' & 'B'.
- 35.2 Indian type squatting pattern water closet: Provide and fix squatting pattern (Indian type) water closet, white with a pair of foot rests, all as specified in Schedule 'A' & 'B'
- 35.3 Wash Basin / Urinal: Provide wash hand basin and flat back urinals all as specified in Schedule A & B. The wash hand basins and squatting pattern shall be fixed all as per manufacturers' instructions.
- 35.4 Testing: All sanitary fittings, waste pipes, vent pipes and SWG pipes etc., shall be tested as approved in MES schedule. The rate quoted for the restive items of Schedule A & B are deemed to include for cost of testing also.
- 35.5 Sanitary and plumbing: General: The contractor shall employ approved licensed plumbers for installation of sanitary fittings and for executing the necessary plumbing works.
- 35.6 Nahani Traps: Where Nahani Traps are indicated in the drawings provide 100mm (Internal) dia cast iron nahani trap with hinged gratings and without let for 75mm dia. pipe. Nahani traps shall be firmly embedded in concrete floors all as directed.

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

- 35.7 Gully trap: Where gully traps are indicated in drawings standard gully trap salt glazed stoneware, with rebated top, strong make, square body, with 150x150mm CI gratings and 100mm dia. outlet shall be provided. Gully trap shall be fixed all as specified in MES schedule and as shown on drawings. The rate quoted for gully trap shall be included for excavation and concrete. PCC type C-1, etc., complete all as specified in Schedule 'A' & 'B'.
- 35.8 SWG PIPE: SWG pipes shall be class-A conforming to is-651 of 1965, SWG pipe shall be laid as directed and shall be jointed all as specified in section – 18, of MES schedule 2004, part I.
- 35.9 Cast iron soil and waste pipes with fittings: CI soil and waste pipes with fitting shall conform to IS-1729-1964. CI soil and waste pipes shall be laid as directed and shall be cement jointed all as specified in Schedule A & B.
- 35.10 Manholes: Manholes independent shall conform to IS 1742 1960 and all as shown on drawing. Brick work shall be in well burnt bricks in cement mortar 1:4 all as specified in MES Schedule And to the thickness shown on drawing. Foundation shall be in PCC 1:3:6 type C-2 with 40mm graded granite stone aggregate for manholes. Benching and channels shall be in PCC 1:2:4 type B-1 using 20mm graded granite stone aggregate, steel trowelled to a smooth and even surface using extra cement. Plastering to brick walls shall be in CM 1:3 15mm thick finished even and fair. All internal surfaces of walls shall be plastered. The external surfaces of walls shall also be plastered to a depth of 150mm from top. The rates quoted by the contractor for manholes shall include for the cot of reinforcement of the Precast cover slab and fixing precast PCC cover slabs of PCC 1:2:4 type B1 for manholes and inspection chamber including PCC 1:2:4 type B-1 bed below the slab removal of surplus spoil to a distance not exc. 50M and any extra excavation and earth work for working space as required.
- 35.11 Testing: All sanitary fittings, waste pipes, vent pipes and SWG pipes etc., shall be tested as provided in MES schedule. The rates quoted for the respective items of Schedule A & B are deemed to include for cost of testing also.
- 36. AC NORTH LIGHT CURVE**  
AC North light curve shall be of approved make and shall be fixed as per manufacturers' instructions and as directed. The net length only shall be measured for payment purpose.
- 37. NORTH LIGHT GLAZING**  
6mm thick wire cast glass shall be fixed in position with aluminium glazing bars as directed and as per manufacturers' instructions. The overall size of north light glazing including the aluminium glazing bars shall be taken into consideration for payment purpose.

***Signature of the Contractor(s) with seal***



## **BEML LIMITED**

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

### **38. AC RADIAL EXHAUST**

AC radial exhaust shall be of 'EVEREST' make or other equivalent and approved make and shall be fixed all as per manufacturer instructions and all as shown on drawing/directed.

### **39. EXPANSION AND CONTRACTION DUMMY JOINTS**

Provide expansion and contraction (Dummy) joints to the width and lengths specified in Schedule 'A' & 'B'. These shall be straight and the slab edges adjacent to the joints shall be formed truly vertical. The top edges of the slab at joints shall be bull nosed to 10mm radius. The joint shall be thoroughly cleaned, sides brushed before filling the filler. The molten bituminous charge before incorporation.

#### **Note:**

- a) All concrete work should be strictly done according to the description and specifications given in the tender. If the same is to be adhered to in respect of any concrete items by the contractors the Engineer in charge shall have the power to reduce the quoted rates in respect of such schedule items and the decision of the Engineer in charge is final and binding on the contractors.
- b) Contractor should note that only the relevant clauses of particular specifications attached to the tender documents are applicable to Schedule A & B- Bill of quantities.

***Signature of the Contractor(s) with seal***





**BEML LIMITED**  
(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

**ACCEPTABLE BRANDS OF MATERIALS**

Sl.No.	Item	Brand/Make
1	Cement	M/s ACC/Ultratech/Birla
2	Paints	M/s Asian Paints/Berger
3	Reinforcement steel	M/s Sail/Tisco/Tata
4	CPVC Pipes	M/s Finolex/Supreme/Astral/Ashrivadh
5	GI pipes	M/s Tata/Zenith
6	PVC	M/s Finolex/Supreme/Prince
7	White cement	M/s Birla/JK
8	Gully trap/Nahani trap	M/s Supreme/Finolex
9	Waterproofing compound	M/s. Fosroc/Roff/BASF
10	Mirror/Toughened/beveled glass	M/s Saintgobain/Modiguard
11	Ceramic/Vitrified tiles	M/s.Johnson/ Kajaria/ Nitco/RAK/Somany
12	Gypsum Board	M/s India Gypsum/Armstrong/Saintgobain
13	Ply wood/Block Board	M/s Archid/Greenply/Century/Kitply.
14	Laminate/Veneer	M/s Archid/Greenply/Century/Kitply.
15	Door closure	M/s Everite/Dorma
16	Locks, mortice locks	M/s. Godrej/Europa
17	Plumbing fittings (Brass Chromium Plated Plumbing fittings)	M/s Parryware/Hindware/ESS ESS/Cera/Jaquar
18	Sanitary Fittings (EWC/IWC/Washbasin)	M/s Jaquar/Hindware/Parryware/Cera
19	u-PVC windows	M/s Fenesta/ Prominance/ Rehau/ Torfenster,
20	VRV/F AC System	M/s Daikin/ Carrier / Hitachi
21	MV Panels, Sub Distribution Board, Bus Bar & Feeder Pillar Etc.	M/s ABB/L&T
22	ACB/MCCB/ELCB/RCCB/MCB	M/s L & T/ABB/Legrand/Schneider/Merlin Gerin
23	HRC Fuses & Fuse Switch Units	M/s L & T/ABB/Legrand/Schneider/Merlin Gerin
24	4P Change Over Switch (On Load)	M/s L & T/ABB/Legrand/Schneider/Merlin Gerin
25	Contactors & O/L Relays	M/s L & T/ABB/Legrand/Schneider/Merlin Gerin
26	Indication Lamps/Push Bottons/Selector Switches	M/s Schneider/ L & T/Siemens/ESSBEE
27	Multifunction Meter –Digital/VAF	M/s Conzerv/Ducati/Elmeasure/Secure/AE
28	Meters	M/s L&T/Conzerv/Secure/AE
29	Transformers	M/s ABC/ Cotsons/ Universal
30	Galvanised iron profile sheet	M/s Tata/Essar/Jindal

**Signature of the Contractor(s) with seal**



**BEML LIMITED**  
(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

Sl.No.	Item	Brand/Make
31	Current Transformers	M/s Kappa/Precise/Gilbert maxweell/Pragati
32	Potential Transformers	M/s Kappa/Precise/Pragati/Automatic Electric
33	FRLS PVC Conduits & Accessories	M/s BEC/CAP/AKG/Precision/Supreme/
34	Switch & Sockets	M/s Anchor Roma/Havells/Crabtree/ABB/Schneider
35	Light & Fixtures	M/s Philips/Havells/Wipro/GE/ Crompton Greaves
36	Fans (Ceiling/wall/Exhaust)	M/s Crompton Greaves /Bajaj/Usha/Havells
37	Aluminium Armoured/Unarmoured cable	M/s Polycab/Havells/KEI
38	Cable glands	M/s HMI/Lotus/Comment
39	TV co axial cable	M/s Delton/Finolex/Skyline
40	Music Speaker Wire (Twin Twisted)	M/s Delton/Finolex/Skyline
41	Telephone cable	M/s Delton/Finolex
42	Floor Outlet Boxes	M/s MK india -EGA
43	Exit Signage	M/s Prolite/Cease fire/MK
44	Cat -5/Cat-6/Voice data	M/s Systimax/AMP
45	TeleTag blocks	M/s Krone
46	Dimming system & sensors	M/s Lutron/Schneider
47	Inverter	M/s Luminous/Su-kam/Microtex
48	Batteries	Exide/AMRON
49	PA Speakers/Amplifier/Mixer/Zone Selection Console	M/s Bosch
50	UPS	M/s Emerson/APC/PCI/Eaton
51	Fire Extinguishers	M/s Ceasfire/Minimax/New Age/Alert
52	Intelligent fire alarm system/Detectors/Manual Call points/Hooters/Speakers/control modules/Monitormodules/graphi csoftware etc.	M/s Morley/Honeywell/Siemens/Edwards
53	Evacuation PA System	M/s Bosch
54	Access Control System	M/s GE/Honeywell/Syris
55	CCTV System	GE/Honeywell/Bosch

\

**Signature of the Contractor(s) with seal**



## **BEML LIMITED**

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

### **GST Terms & Conditions**

1. The Supplier is required to comply with all the applicable provisions of the GST Laws/Rules/Notifications/Circulars and to furnish required documents/details within the prescribed time limit to enable BEML to claim the benefits of GST Input Tax Credit or any other benefit.
2. The Supplier is required to furnish proper Invoice/Supplementary Invoice/Debit Note/Credit Note in the form and manner prescribed under GST Laws/Rules/Notifications/Circulars containing all the particulars mentioned therein and within the prescribed time limit as per prevailing GST Laws/Rules/Notifications/Circulars. In case of non-compliance by the Supplier, BEML shall not make any payment towards GST against such invoice until it is complied with within the timeline prescribed under GST Laws/Rules/Notifications/Circulars, and also subject to BEML being in a position to avail GST Input Tax Credit as per applicable GST Laws/Rules/Notifications/Circulars.
3. In case of discrepancy in the data uploaded by the Supplier in the GSTN portal or in case of any shortages or rejection in the supply, BEML will notify the Supplier of the same. Supplier has to rectify the data discrepancy in the GSTN portal or issue Credit note (details to be uploaded in GSTN portal) for the shortages or rejections in the supplies, within the prescribed time limit to enable BEML to avail GST Input Tax Credit.
4. In case, the availment of GST Input Tax Credit by BEML is delayed for any reason other than those attributable to BEML, interest at applicable rate as prescribed under GST Laws/Rules/Notifications/Circulars for such delays shall be recovered from the Supplier.
5. In case Supplier delays declaring such invoice in his GST Return and GST Input Tax Credit availed by BEML is denied or reversed subsequently as per GST Laws/Rules/Notifications/Circulars, GST amount paid by BEML towards such reversal as per GST Laws/Rules/Notifications/Circulars shall be recoverable from Supplier along with applicable interest.
6. If BEML has not paid/short paid to the Supplier for any invoices within the time limit prescribed under GST Laws/Rules/Notifications/Circulars due to non-compliance of GST Laws/Rules/Notifications/Circulars by Supplier or any other reason attributable to Supplier and leads to any GST Input Tax Credit reversal by BEML, any losses/expenses/cost/penalty, etc incurred by BEML shall be recoverable from the Supplier.
7. Wherever applicable, BEML will have the right to deduct "Tax Deducted at Source" at the rate prescribed under the GST Laws/Rules/Notifications/Circulars and to remit the same to the Government.

***Signature of the Contractor(s) with seal***



## BEML LIMITED

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

8. In case of supplies made under Reverse Charge Mechanism, the Supplier needs to comply with the provisions under the GST Laws/Rules/Notifications/Circulars in terms of supply of Goods/Services and raising of invoice, so as to enable BEML to remit applicable GST to Govt., within the prescribed time limit and avail GST Input Tax Credit on the same. If the Supplier fails to comply with the above and as a result if BEML incurs any losses/expenses/cost/penalty, BEML shall be entitled to recover the same from the Supplier. Further the Supplier has to mention that “the liability of payment of GST amounting to Rs ..... is on the Recipient of Service” in the invoice raised on BEML.
9. The Supplier is required to comply with the E-Way Bill Provisions under GST Laws/Rules/Notifications/Circulars. If the Supplier fails to comply with the said provisions and as a result if BEML incurs any losses/expenses/cost/penalty, BEML shall be entitled to recover the same from the Supplier.
10. In case of materials/goods issued to Supplier for Job Work, the Job Work Supplier is required to return the goods within the time limit prescribed in the Purchase Order. If the Job Work Supplier fails to return the goods as above, BEML will be entitled to raise a GST Supply Invoice on the Job Worker Supplier with applicable interest as per the provisions of GST Laws/Rules/Notifications/Circulars. In such cases, BEML will be entitled to recover all such GST/interest on GST /losses/expenses/cost/penalty, etc. incurred by BEML along with interest from the Job Work Supplier. Further in such cases where the GST invoice has been raised by BEML, on return of such goods after the prescribed time limit, the Job Work Supplier needs to return the same under GST invoice.
11. GST portion of the invoice shall be released only upon the Supplier declaring such invoice in his GST Return and payment of GST thereof to appropriate government and satisfying all the conditions mentioned above. However, in case the Supplier wishes to obtain the payment of GST portion also along with the payment of the base value of the invoice, Supplier has the option to submit Bank Guarantee of an amount equivalent to the GST portion of the invoice plus 3 months’ interest at prevailing rate of interest under GST Laws/Rules/Notifications/Circulars as applicable in case of reversal of GST Input Tax Credit. Such Bank Guarantee shall be valid till 30<sup>th</sup> September of the next financial year or filing of GST Annual Return by Supplier/Vendor (for which such invoice pertains to), whichever is earlier. BEML will release Bank Guarantee only when the Supplier declaring such invoice in his GST Return and remittance of GST thereon to the Govt. In case the Supplier fails to fulfill the required conditions resulting in BEML not been able to avail GST Input Tax Credit Bank Guarantee shall be encashed and such GST amount along with interest and any other cost/loss incurred by BEML shall be recoverable from Supplier.
12. The Supplier have the option to give one Bank Guarantee of appropriate value after considering his estimated value of GST involved in invoices raised on BEML instead of Bank Guarantee for each Contract/Invoice. In case of payment through LC, suitable provisions/clause will be inserted while opening LC to ensure compliances of above conditions. However, if at any point of time value of such Bank Guarantee falls short of GST plus interest thereof, Supplier will have to either furnish Bank Guarantee for

***Signature of the Contractor(s) with seal***



## **BEML LIMITED**

(A Government of India Undertaking)  
206/D1, Bhagirathi, Rameshwaram Colony,  
Bariatu Road, Ranchi-834009  
Jharkhand, India

Differential value or such shortfall value of Bank Guarantee vis-à-vis GST plus interest thereof shall be withheld till Suppliers fulfil its obligations specified under above clauses.

13. BEML will be entitled to recover all losses/expenses/cost/penalty, etc. incurred by BEML along with applicable interest from the Supplier due to reasons other than those attributable to BEML.
14. If the Supplier is a Composition/Unregistered Dealer, the Supplier needs to comply with the provisions under the GST Laws/Rules/Notifications/Circulars in terms of supply of Goods/Service and raising of invoice. In case, the Supplier fails to comply with the above and as a result if BEML incurs any losses/expenses/cost/penalty, BEML shall be entitled to recover the same from the Supplier along with applicable interest.

***Signature of the Contractor(s) with seal***

Name of Work:	Repairing and Renovation of Storage at Koker Ranchi	SCHEDULE A	
PART A (CIVIL REPAIR/RENOVATION)			
ITEM NUMBER	Item Description	Quantity	Units
1	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.Nominal concrete 1:3:6 or richer mix (i/c equivalent design mix) DSR- 15.2.1	42.37	Sqm
2	Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar DSR-15.7.4	2.48	Cum
3	Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer - in- charge. DSR-15.3	1.70	Sqm
4	Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead : Of area 3 sq. metres and below DSR-15.12.1	31.00	Each
5	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge. DSR-14.1.1	247.34	Sqm
6	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.. DSR-13.91	1236.70	Sqm
7	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete .. DSR-13.88	712.47	Sqm

10	<p>Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For fixed portion. Powder coated aluminium (minimum thickness of powder coating 50 micron) (DSR. 21.1.1.2)</p>	21.25	Kg
11	<p>Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For shutters of doors, windows &amp; ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately). Powder coated aluminium (minimum thickness of powder coating 50 micron) (DSR 21.1.2.2)</p>	36.80	Kg

12	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item):. With float glass panes of 4.0 mm thickness (DSR. 21.3.1)	47.25	Sqm
13	Distemping with oil bound washable distemper of approved brand and manufacture to give an even shade : New work (two or more coats) over and including water thinnable priming coat with cement primer (DSR . 13.41.1)	565.24	Sqm
14	Finishing walls with Acrylic Smooth exterior paint of required shade : New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm) (CPWD DSR. 13.46.1)	671.46	Sqm
15	Colour washing such as green, blue or buff to give an even shade : New work (two or more coats) with a base coat of white washing with lime DSR 13.39.1	712.47	Sqm
16	Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, fillets, sunken floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing: 1:1½:3 (1 cement : 1½ coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources). DSR-4.2.2	2.35	Cum
17	Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. including priming coat with approved steel primer all completeFixed to openings /wooden frames with rawl plugs screws etc DSR .9.48.2	123.50	Kg
18	Dismantling steel work in built up sections in angles, tees, flats and channels including all gusset plates, bolts, nuts, cutting rivets, welding etc. including dismembering and stacking within 50 metres lead. DSR-15.18	2870.64	Kg
19	Structural steel work in single section, fixed with or without connecting plate, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.DSR-10.1	3488.02	Kg



20	Brick work with common burnt clay machine moulded perforated bricks of class designation 12.5 conforming to IS: 2222 in superstructure above plinth level up to floor five level in cement mortar 1:6 (1 cement : 6 coarse sand) With Modular bricks DSR-6.3.2	2.99	Cum
21	Cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 40 mm nominal size) in pavements, laid to required slope and camber in panels as required including consolidation finishing and tamping complete. (DSR- 16.42)	72.63	Cum
22	Centering and shuttering including strutting, propping etc. and removal of form work for : Foundations, footings, bases for columns DSR-4.3.1	39.44	Sqm
23	Disposal of moorum/building rubbish/ malba/ similar unserviceable, dismantled or waste material by mechanical transport including loading, transporting, unloading to approved municipal dumping ground for lead upto 10 km for all lifts, complete as per directions of Engineer-in-charge. DSR-1.1.18	46.55	Cum

**PART B (ELECTRICAL WORKS)**

1	Supplying and fixing following piano type switch/ socket on the existing switch box/ cover including connections etc. as required. 5/6 amps switch. (CPWD E&M SOR22, Item No. 1.23.1)	10.00	Each
2	Supplying and fixing following piano type switch/ socket on the existing switch box/ cover including connections etc. as required. 15/16 amp switch. (CPWD E&M SOR22, Item No. 1.23.3)	10.00	Each
3	Supplying and fixing following piano type switch/ socket on the existing switch box/ cover including connections etc. as required. 3 pin 5/6 amp socket outlet. (CPWD E&M SOR22, Item No. 1.23.4)	10.00	Each
4	Supplying and fixing following piano type switch/ socket on the existing switch box/ cover including connections etc. as required. 6 pin 15/16 amp socket outlet. (CPWD E&M SOR22, Item No. 1.23.5)	10.00	Each
5	Supplying and fixing 5 amps to 32 amps rating, 240/415 volts, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required. Single pole. (CPWD E&M SOR22, Item No. 2.10.1)	5.00	Each

6	Supplying and fixing 5 amps to 32 amps rating, 240/415 volts, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required. Single pole and neutral. (CPWD E&M SOR22, Item No. 2.10.2)	5.00	Each
7	Supplying and fixing following rating, four pole, 415 volts, isolator in the existing MCB DB complete with connections, testing and commissioning etc. as required. 100 amps. (CPWD E&M SOR22, Item No. 2.13.3)	2.00	Each
8	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit, with piano type switch, phenolic laminated sheet, suitable size M.S. box and earthing the point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc. as required. Group A. (CPWD E&M SOR22, Item No. 1.8.1)	15.00	Point
9	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit, with piano type switch, phenolic laminated sheet, suitable size M.S. box and earthing the point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc. as required. Group B. (CPWD E&M SOR22, Item No. 1.8.2)	10.00	Point
10	Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FRLS PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required. 2 X 1.5 sq. mm + 1 X 1.5 sq. mm earth wire. (CPWD E&M SOR22, Item No. 1.14.1)	50.00	Metre
11	Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FRLS PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required. 2 X 2.5 sq. mm + 1 X 2.5 sq. mm earth wire. (CPWD E&M SOR22, Item No. 1.14.2)	100.00	Metre
12	Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FRLS PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required. 2 X 4 sq. mm + 1 X 4 sq. mm earth wire. (CPWD E&M SOR22, Item No. 1.14.3)	50.00	Metre

13	Supplying and fixing of following sizes of medium class PVC conduit along with accessories in surface/recess including cutting the wall and making good the same in case of recessed conduit as required. 20 mm (CPWD E&M SOR22, Item No. 1.21.1)	100.00	Metre
14	Supplying and fixing 3 pin, 5 amp ceiling rose on the existing junction box/ wooden block including connection etc as required. (CPWD E&M SOR22, Item No. 1.33)	5.00	Each
15	Supplying and fixing stepped type electronic fan regulator on the existing modular plate switch box including connections but excluding modular plate etc. as required. (CPWD E&M SOR22, Item No. 1.25)	5.00	Each
16	Supply and fixing following way single pole neutral, sheet steel, MCB distribution board 240 volts, on surface/recessed complete with tinned copper busbars, neutral busbar, earth bar, din bar, detachable gland plate, interconnections, phosphotized & powder painted including earthing etc. as required (But without MCB/RCCB/Isolator). 12 way single door	5.00	No.
17	Supplying of following way, single pole and neutral, sheet steel, MCB distribution board, 415 volts on surface/recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, detachable gland plate, interconnection, phosphatized and powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator). 4 way (4+12), double door, Horizontal type	5.00	Each
18	Supply and fixing of PVC board size 4"x4" with parpex sheet cover (75 mm x 75 mm x 50 mm)	5.00	No.
19	Supply and fixing of PVC board size 7"x4" with parpex sheet cover (72 mm x 146 mm x 48 mm)	5.00	No.
20	Supply and fixing of PVC board size 8"x6" with parpex sheet cover (121 mm x 173 mm x 48 mm)	5.00	No.
21	Supply and fixing of PVC board size 8"x12" with parpex sheet cover (210 mm x 206 mm x 48 mm)	5.00	No.
22	Providing and fixing of 20 watt LED tube with box type fitting as per instruction of EIC.	10.00	No.
23	Providing and fixing of ceiling fan 48 inch ceiling fan as per instruction of EIC.	5.00	No.
24	Providing and fixing of Exhaust fan 230 mm as per instruction of EIC.	5.00	No.
25	Providing and fixing of 30 watt LED street light as per instruction of EIC.	20.00	No.
26	Providing and fixing of 50 mm dia MS pipe for fixing of street light as per instruction of EIC.	20.00	Metre

Name of Work:	Construction of New Toilet at Kokar, Ranchi	SCHEDULE B	
Part A (Civil Construction)			
ITEM NUMBER	Item Description	Quantity	Units
1	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All kinds of soil. (DSR-2.8.1)	33.75	Cum
2	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m. (DSR- 2.25)	10.13	Cum
3	Supplying and filling in plinth with Jamuna sand under floors, including watering, ramming, consolidating and dressing complete. (DSR- 2.27)	2.25	Cum
4	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level: 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) (DSR- 4.1.3)	1.80	Cum
5	Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15° landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases above plinth level up to floor five level, excluding the cost of centering, shuttering, finishing and reinforcement with 1:1.5:3 (1 cement : 1.5 coarse sand(zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources.) (DSR- 5.3)	3.72	Cum
6	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level :1:1.5:3 (1 cement : 1.5 coarse sand	5.06	Cum
7	Reinforced cement concrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts etc. up to floor five level, excluding cost of centering, shuttering, finishing and reinforcement : 1:1.5:3 (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size) (DSR- 5.2.2)	1.50	Cum
8	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level. Thermo-Mechanically Treated bars (DSR- 5.22.6)	800.00	Kg

9	Centering and shuttering including strutting, propping etc. and removal of form for : Lintels, beams, plinth beams, girders, bressumers and cantilevers (DSR- 5.9.5)	13.30	Sqm
10	Centering and shuttering including strutting, propping etc. and removal of form for : Columns, Pillars, Piers, Abutments, Posts and Struts (DSR- 5.9.6)	31.50	Sqm
11	Suspended floors, roofs, landings, balconies and access platform DSR-9.3	19.35	Sqm
12	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 5 in superstructure above plinth level up to floor V level in all shapes and sizes in : Cement mortar 1:6 (1cement : 6coarse sand) (DSR- 6.4.2 DR)	17.69	Cum
13	12 mm cement plaster of mix : 1:6 (1cement: 6fine sand) (DSR- 13.1.2)	157.80	Sqm
14	Finishing walls with Acrylic Smooth exterior paint of required shade : New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm) (DSR- 13.46.1)	157.80	Sqm
15	Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement : 4 Coarse sand), Jointing with grey cement slurry @ 3.3 kg/sqm including pointing the joints with white cement and matching pigment etc., complete. DRS-11 37	16.00	Sqm
16	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete DSR-8.31	36.48	Sqm

17	<p>Providing and fixing factory made P.V.C. door frame of size 50x47 mm with a wall thickness of 5 mm, made out of extruded 5mm rigid PVC foam sheet, mitred at corners and joined with 2 Nos of 150 mm long brackets of 15x15 mm M.S. square tube, the vertical door frame profiles to be reinforced with 19x19 mm M.S. square tube of 19 gauge, EPDM rubber gasket weather seal to be provided through out the frame. The door frame to be fixed to the wall using M.S. screws of 65/100 mm size, complete as per manufacturer's specification and direction of Engineer- in-Charge. (DSR- 9.119)</p>	9.90	Mtr
18	<p>Providing and fixing factory made panel PVC door shutter consisting of frame made out of M.S. tubes of 19 gauge thickness and size of 19 mm x 19 mm for styles and 15x15 mm for top &amp; bottom rails. M.S. frame shall have a coat of steel primers of approved make and manufacture . M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75 mm shall be flat and 20 mm shall be tapered in 45 degree on the inner side to form top and bottom rail and 115 mm wide PVC sheet out of which 75 mm shall be flat and 20 mm shall be tapered on both sides to form lock rail. Top, bottom and lock rails shall be provided both side of the panel. 10 mm (5 mm x 2 ) thick, 20 mm wide cross PVC sheet be provided as gap insert for top rail &amp; bottom rail, paneling of 5 mm thick both side PVC sheet to be fitted in the M.S. frame welded/ sealed to the styles &amp; rails with 7 mm (5 mm+2 mm) thick x 15 mm wide PVC sheet beading on inner side, and joined together with solvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete as per direction of Engineer-in-charge, manufacturer's</p>	2.85	Sqm

19	<p>Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete As per Architectural Drawing work is Excuted hence qty is Deviateds and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For fixed portion. Powder coated aluminium (minimum thickness of powder coating 50 micron) (DSR-21.1.1.2)</p>	8.06	Kg
20	<p>Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete As per Architectural Drawing work is Excuted hence qty is Deviateds and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For shutters of doors, windows &amp; ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately). Powder coated aluminium (minimum thickness of powder coating 50 micron) (DSR- 21.1.2.2)</p>	8.06	Kg
21	<p>Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item):. With float glass panes of 4.0 mm thickness (DSR- 21.3.1)</p>	2.62	Sqm

22	Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills , facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels. Granite of any colour and shade Area of slab over 0.50 sqm. (DSR- 8.2.2.2)	2.52	Sqm
23	Providing and fixing aluminium pull bolt lock, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade, with necessary screws bolts, nut and washers etc. complete.(DSR- 9.98)	4.00	Each
24	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes. 110 mm diameter (DSR- 12.41.2)	20.00	Mtr
25	Providing and fixing unplasticised - PVC pipe clips of approved design to unplasticised - PVC rain water pipes by means of 50x50x50 mm hard wood plugs, screwed with M.S. screws of required length,including cutting brick work and fixing in cement mortar 1:4 (1 cement: 4 coarse sand) and making good the wall etc. complete. 110 mm (DSR- 12.43.2)	10.00	Each
26	Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion. Bend 87.5° 110 mm bend (DSR- 12.42.5.2)	5.00	Each
27	Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion. Single tee with door 110x110x110 mm. (DSR- 12.42.3.2)	5.00	Each
28	Making plinth protection 50 mm thick of cement concrete 1:3:6 (1cement: 3coarse sand : 6graded stone aggregate 20 mm nominal size) over 75mm thick bed of dry brick ballast 40 mm nominal size, well rammed and consolidated and grouted with fine sand, including finishing the top smooth. (DSR- 4.17)	13.20	Sqm



<b>PART B (WATER SUPPLY &amp; SANITARY)</b>			
1	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc. : 20 mm nominal outer dia Pipes (DSR-18.8.2)	15.00	Mtr
2	Providing and fixing G.I. pipes complete with G.I. fittings including trenching and refilling etc. External work : 40 mm dia nominal bore. (DSR- 18.12.5)	10.00	Mtr
3	Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931 : 15 mm nominal bore (DSR-18.49.1)	2.00	Each
4	Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm and 340x410x265 mm sizes respectively with automatic flushing cistern with standard flush pipe and C.P. brass spreaders with brass unions and G.I clamps complete, including painting of fittings and brackets, cutting and making good the walls and floors wherever required : Range of two urinal basins with 5 litre white P.V.C. automatic flushing cistern. (DSR- 17.4.2)	3.00	Each
5	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required : W.C. pan with ISI marked white solid plastic seat and lid W.C. pan with ISI marked black solid plastic seat and lid. (DSR- 17.2.2)	2.00	Each
6	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require : White Vitreous China Wash basin size 550x400 mm with a pair of 15 mm C.P. brass pillar taps. (DSR-17.7.3)	3.00	Each
7	Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass screws and washers complete. (DSR- 17.31)	3.00	Each

8	Providing and fixing 600x120x5 mm glass shelf with edges round off, supported on anodised aluminium angle frame with C.P. brass brackets and guard rail complete fixed with 40 mm long screws, rawl plugs etc., complete. (DSR- 17.33)	2.00	Each
9	Providing and fixing PTMT liquid soap container 109 mm wide, 125 mm high and 112 mm distance from wall of standard shape with bracket of the same materials with snap fittings of approved quality and colour, weighing not less than 105 gms. (DSR- 17.71)	2.00	Each
10	Providing and fixing PTMT towel rail complete with brackets fixed to wooden cleats with CP brass screws with concealed fittings arrangement of approved quality and colour. 450 mm long towel rail with total length of 495 mm, 78 mm wide and effective height of 88 mm, weighing not less than 170 gms (DSR- 17.73.1)	2.00	Each
11	Providing and fixing uplasticised PVC connection pipe with brass unions : 30 cm length : 15 mm nominal bore (DSR- 18.21.1.1)	13.00	Mtr
12	Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete. Semi rigid pipe 32 mm dia (DSR- 17.28.1.1)	13.00	Each
13	Providing and placing on terrace (at all floor levels) polyethylene water storage tank, ISI : 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. (DSR- 18.48)	1000.00	Ltr
14	Constructing brick masonry chamber for underground C.I. inspection chamber and bends with bricks in cement mortar 1:4 (1 cement : 4 coarse sand) C.I. cover with frame (light duty) 455x610 mm internal dimensions, total weight of cover with frame to be not less than 38 kg (weight of cover 23 kg and weight of frame 15 kg), R.C.C. top slab with 1:2:4 mix (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size), foundation concrete 1:5:10 (1 cement : 5 fine sand : 10 graded stone aggregate 40 mm nominal size), inside plastering 12 mm thick with cement mortar 1:3 (1 cement : 3 coarse sand), finished smooth with a floating coat of neat cement on walls and bed concrete etc. complete as per standard design : Inside dimensions 455x610 mm and 45 cm deep for single pipe line : With common burnt clay F.P.S. (non modular) bricks of class designation 5 (DSR- 19.30.1.1 DR)	2.00	Each
15	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end) :		
	40 mm nominal bore DSR-18.17.3	1.00	Nos

16	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end) :		
	20 mm nominal bore DSR-18.17.1A	2.00	Nos
17	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931		
	15mm nominal bore DSR-18.53.1	5.00	Nos
18	Providing and fixing PTMT grating of approved quality and colour. Circular type 100 mm nominal dia DSR-18.58.1.1	9.00	Nos
	<b>PART C (ELECTRICAL PORTION)</b>		
1	Supplying and fixing following piano type switch/ socket on the existing switch box/ cover including connections etc. as required. 5/6 amps switch. (CPWD E&M SOR-2022, Item No. 1.23.1)	5.00	Each
2	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit, with piano type switch, phenolic laminated sheet, suitable size M.S. box and earthing the point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc. as required. Group A. (CPWD E&M SOR-2022, Item No. 1.8.1)	5.00	Point
3	Supplying and fixing following piano type switch/ socket on the existing switch box/ cover including connections etc. as required. 3 pin 5/6 amp socket outlet. (CPWD E&M SOR22, Item No. 1.23.4)	5.00	Each
4	Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FRLS PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required. 2 X 1.5 sq. mm + 1 X 1.5 sq. mm earth wire. (CPWD E&M SOR-2022, Item No. 1.14.1)	50.00	Metre
5	Supply and fixing of PVC board size 4"x4" with parpex sheet cover (75 mm x 75 mm x 50 mm)	5.00	No.
6	Providing and fixing of 20 watt LED tube with box type fitting as per instruction of EIC.	5.00	No.
7	Providing and fixing of Exhaust fan 230 mm as per instruction of EIC.	7.00	No.

Name of Work:		Repairing and Renovation of Storage at Koker Ranchi			SCHEDULE C	
PART A (CIVIL REPAIR & RENOVATION)						
ITEM NUMBER	Item Description	Quantity	Units	Rate in Rs. P	Amount	
1	Demolishing cement concrete manually/ by mechanical means including disposal of material within 50 metres lead as per direction of Engineer - in - charge.Nominal concrete 1:3:6 or richer mix (i/c equivalent design mix) DSR- 15.2.1	42.37	Cum			
2	Demolishing brick work manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge. In cement mortar DSR-15.7.4	2.48	Cum			
3	Demolishing R.C.C. work manually/ by mechanical means including stacking of steel bars and disposal of unserviceable material within 50 metres lead as per direction of Engineer - in- charge. DSR-15.3	1.70	Sqm			
4	Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead : Of area 3 sq. metres and below DSR-15.12.1	31.00	Each			
5	Repairs to plaster of thickness 12 mm to 20 mm in patches of area 2.5 sq.meters and under, including cutting the patch in proper shape, raking out joints and preparing and plastering the surface of the walls complete, including disposal of rubbish to the dumping ground, all complete as per direction of Engineer-in-Charge. DSR-14.1.1	247.34	Sqm			
6	Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete.. DSR-13.91	1236.70	Sqm			
7	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete .. DSR-13.88	712.47	Sqm			
10	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For fixed portion. Powder coated aluminium (minimum thickness of powder coating 50 micron) (DSR. 21.1.1.2)	21.25	Kg			

11	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately). Powder coated aluminium (minimum thickness of powder coating 50 micron) (DSR 21.1.2.2)	36.80	Kg		
12	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item):. With float glass panes of 4.0 mm thickness (DSR 21.3.1)	47.25	Sqm		
13	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade : New work (two or more coats) over and including water thinnable priming coat with cement primer (DSR . 13.41.1)	565.24	Sqm		
14	Finishing walls with Acrylic Smooth exterior paint of required shade : New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm) (CPWD DSR. 13.46.1)	671.46	Sqm		
15	Colour washing such as green, blue or buff to give an even shade : New work (two or more coats) with a base coat of white washing with lime DSR 13.39.1	712.47	Sqm		
16	Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, fillets, sunken floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing: 1:1½:3 (1 cement : 1½ coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources). DSR-4.2.2	2.35	Cum		
17	Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. including priming coat with approved steel primer all completeFixed to openings /wooden frames with rawl plugs screws etc DSR .9.48.2	123.50	Kg		

18	Dismantling steel work in built up sections in angles, tees, flats and channels including all gusset plates, bolts, nuts, cutting rivets, welding etc. including dismembering and stacking within 50 metres lead. DSR-15.18	2870.64	Kg		
19	Structural steel work in single section, fixed with or without connecting plate, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.DSR-10.1	3488.02	Kg		
20	Brick work with common burnt clay machine moulded perforated bricks of class designation 12.5 conforming to IS: 2222 in superstructure above plinth level up to floor five level in cement mortar 1:6 (1 cement : 6 coarse sand) With Modular bricks DSR-6.3.2	2.99	Cum		
21	Cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 40 mm nominal size) in pavements, laid to required slope and camber in panels as required including consolidation finishing and tamping complete. (DSR- 16.42)	72.63	Cum		
22	Centering and shuttering including strutting, propping etc. and removal of form work for : Foundations, footings, bases for columns DSR-4.3.1	39.44	Sqm		
23	Disposal of moorum/building rubbish/ malba/ similar unserviceable, dismantled or waste material by mechanical transport including loading, transporting, unloading to approved municipal dumping ground for lead upto 10 km for all lifts, complete as per directions of Engineer-in-charge. DSR-1.1.18	46.55	Cum		
<b>PART B (ELECTRICAL WORKS)</b>					
1	Supplying and fixing following piano type switch/ socket on the existing switch box/ cover including connections etc. as required. 5/6 amps switch. (CPWD E&M SOR22, Item No. 1.23.1)	10.00	Each		
2	Supplying and fixing following piano type switch/ socket on the existing switch box/ cover including connections etc. as required. 15/16 amp switch. (CPWD E&M SOR22, Item No. 1.23.3)	10.00	Each		
3	Supplying and fixing following piano type switch/ socket on the existing switch box/ cover including connections etc. as required. 3 pin 5/6 amp socket outlet. (CPWD E&M SOR22, Item No. 1.23.4)	10.00	Each		
4	Supplying and fixing following piano type switch/ socket on the existing switch box/ cover including connections etc. as required. 6 pin 15/16 amp socket outlet. (CPWD E&M SOR22, Item No. 1.23.5)	10.00	Each		
5	Supplying and fixing 5 amps to 32 amps rating, 240/415 volts, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required. Single pole. (CPWD E&M SOR22, Item No. 2.10.1)	5.00	Each		
6	Supplying and fixing 5 amps to 32 amps rating, 240/415 volts, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required. Single pole and neutral. (CPWD E&M SOR22, Item No. 2.10.2)	5.00	Each		
7	Supplying and fixing following rating, four pole, 415 volts, isolator in the existing MCB DB complete with connections, testing and commissioning etc. as required. 100 amps. (CPWD E&M SOR22, Item No. 2.13.3)	2.00	Each		

8	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit, with piano type switch, phenolic laminated sheet, suitable size M.S. box and earthing the point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc. as required. Group A. (CPWD E&M SOR22, Item No. 1.8.1)	15.00	Point		
9	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit, with piano type switch, phenolic laminated sheet, suitable size M.S. box and earthing the point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc. as required. Group B. (CPWD E&M SOR22, Item No. 1.8.2)	10.00	Point		
10	Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FRLS PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required. 2 X 1.5 sq. mm + 1 X 1.5 sq. mm earth wire. (CPWD E&M SOR22, Item No. 1.14.1)	50.00	Metre		
11	Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FRLS PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required. 2 X 2.5 sq. mm + 1 X 2.5 sq. mm earth wire. (CPWD E&M SOR22, Item No. 1.14.2)	100.00	Metre		
12	Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FRLS PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required. 2 X 4 sq. mm + 1 X 4 sq. mm earth wire. (CPWD E&M SOR22, Item No. 1.14.3)	50.00	Metre		
13	Supplying and fixing of following sizes of medium class PVC conduit along with accessories in surface/recess including cutting the wall and making good the same in case of recessed conduit as required. 20 mm (CPWD E&M SOR22, Item No. 1.21.1)	100.00	Metre		
14	Supplying and fixing 3 pin, 5 amp ceiling rose on the existing junction box/ wooden block including connection etc as required. (CPWD E&M SOR22, Item No. 1.33)	5.00	Each		
15	Supplying and fixing stepped type electronic fan regulator on the existing modular plate switch box including connections but excluding modular plate etc. as required. (CPWD E&M SOR22, Item No. 1.25)	5.00	Each		
16	Supply and fixing following way single pole neutral, sheet steel, MCB distribution board 240 volts, on surface/ recessed complete with tinned copper busbas, neutral busbar, earth bar, din bar, detactable gland plate, interconnections, phospotized & powder painted including earthing etc. as required (But without MCB/RCCB/Isolator). 12 way single door	5.00	No.		

17	Supplying of following way, single pole and neutral, sheet steel, MCB distribution board, 415 volts on surface/recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, detachable gland plate, interconnection, phosphatized and powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator). 4 way (4+12), double door, Horizontal type	5.00	Each		
18	Supply and fixing of PVC board size 4"x4" with parpex sheet cover (75 mm x 75 mm x 50 mm)	5.00	No.		
19	Supply and fixing of PVC board size 7"x4" with parpex sheet cover (72 mm x 146 mm x 48 mm)	5.00	No.		
20	Supply and fixing of PVC board size 8"x6" with parpex sheet cover (121 mm x 173 mm x 48 mm)	5.00	No.		
21	Supply and fixing of PVC board size 8"x12" with parpex sheet cover (210 mm x 206 mm x 48 mm)	5.00	No.		
22	Providing and fixing of 20 watt LED tube with box type fitting as per instruction of EIC.	10.00	No.		
23	Providing and fixing of ceiling fan 48 inch ceiling fan as per instruction of EIC.	5.00	No.		
24	Providing and fixing of Exhaust fan 230 mm as per instruction of EIC.	5.00	No.		
25	Providing and fixing of 30 watt LED street light as per instruction of EIC.	20.00	No.		
26	Providing and fixing of 50 mm dia MS pipe for fixing of street light as per instruction of EIC.	20.00	Metre		
<b>Total in Figures = Rs</b>					



Name of Work:		Construction of New Toilet at Koker, Ranchi			SCHEDULE D	
PART A (CIVIL CONSTRUCTION)						
ITEM NUMBER	Item Description	Quantity	Units	Rate in Rs. P	Amount	
1	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan), including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All kinds of soil. (DSR-2.8.1)	33.75	Cum			
2	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m. (DSR- 2.25)	10.13	Cum			
3	Supplying and filling in plinth with Jamuna sand under floors, including watering, ramming, consolidating and dressing complete. (DSR- 2.27)	2.25	Cum			
4	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level: 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) (DSR- 4.1.3)	1.80	Cum			
5	Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15° landings, balconies, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases above plinth level up to floor five level, excluding the cost of centering, shuttering, finishing and reinforcement with 1:1.5:3 (1 cement : 1.5 coarse sand(zone-III) derived from natural sources : 3 graded stone aggregate 20 mm nominal size derived from natural sources.) (DSR- 5.3)	3.72	Cum			
6	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level :1:1.5:3 (1 cement : 1.5 coarse sand	5.06	Cum			
7	Reinforced cement concrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts etc. up to floor five level, excluding cost of centering, shuttering, finishing and reinforcement : 1:1.5:3 (1 cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size) (DSR- 5.2.2)	1.50	Cum			
8	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level. Thermo-Mechanically Treated bars (DSR- 5.22.6)	800.00	Kg			
9	Centering and shuttering including strutting, propping etc. and removal of form for : Lintels, beams, plinth beams, girders, bressumers and cantilevers (DSR- 5.9.5)	13.30	Sqm			
10	Centering and shuttering including strutting, propping etc. and removal of form for : Columns, Pillars, Piers, Abutments, Posts and Struts (DSR- 5.9.6)	31.50	Sqm			
11	Suspended floors, roofs, landings, balconies and access platform DSR-9.3	19.35	Sqm			

12	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 5 in superstructure above plinth level up to floor V level in all shapes and sizes in : Cement mortar 1:6 (1cement : 6coarse sand) (DSR- 6.4.2 DR)	17.69	Cum		
13	12 mm cement plaster of mix : 1:6 (1cement: 6fine sand) (DSR- 13.1.2)	157.80	Sqm		
14	Finishing walls with Acrylic Smooth exterior paint of required shade : New work (Two or more coat applied @ 1.67 ltr/10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm) (DSR- 13.46.1)	157.80	Sqm		
15	Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement : 4 Coarse sand), Jointing with grey cement slurry @ 3.3 kg/sqm including pointing the joints with white cement and matching pigment etc., complete. DRS-11 37	16.00	Sqm		
16	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete DSR-8.31	36.48	Sqm		
17	Providing and fixing factory made P.V.C. door frame of size 50x47 mm with a wall thickness of 5 mm, made out of extruded 5mm rigid PVC foam sheet, mitred at corners and joined with 2 Nos of 150 mm long brackets of 15x15 mm M.S. square tube, the vertical door frame profiles to be reinforced with 19x19 mm M.S. square tube of 19 gauge, EPDM rubber gasket weather seal to be provided through out the frame. The door frame to be fixed to the wall using M.S. screws of 65/100 mm size, complete as per manufacturer's specification and direction of Engineer- in-Charge. (DSR- 9.119)	9.90	Mtr		

18	<p>Providing and fixing factory made panel PVC door shutter consisting of frame made out of M.S. tubes of 19 gauge thickness and size of 19 mm x 19 mm for styles and 15x15 mm for top &amp; bottom rails. M.S. frame shall have a coat of steel primers of approved make and manufacture . M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75 mm shall be flat and 20 mm shall be tapered in 45 degree on the inner side to form top and bottom rail and 115 mm wide PVC sheet out of which 75 mm shall be flat and 20 mm shall be tapered on both sides to form lock rail. Top, bottom and lock rails shall be provided both side of the panel. 10 mm (5 mm x 2 ) thick, 20 mm wide cross PVC sheet be provided as gap insert for top rail &amp; bottom rail, paneling of 5 mm thick both side PVC sheet to be fitted in the M.S. frame welded/ sealed to the styles &amp; rails with 7 mm (5 mm+2 mm) thick x 15 mm wide PVC sheet beading on inner side, and joined together with solvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete as per direction of Engineer-in-charge, manufacturer's</p>	2.85	Sqm		
19	<p>Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete As per Architectural Drawing work is Excuted hence qty is Deviateds and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For fixed portion. Powder coated aluminium (minimum thickness of powder coating 50 micron) (DSR-21.1.1.2)</p>	8.06	Kg		

20	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete As per Architectural Drawing work is Excuted hence qty is Deviateds and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately). Powder coated aluminium (minimum thickness of powder coating 50 micron) (DSR- 21.1.2.2)	8.06	Kg		
21	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item):. With float glass panes of 4.0 mm thickness (DSR- 21.3.1)	2.62	Sqm		
22	Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills , facias and similar locations of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4 coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels. Granite of any colour and shade Area of slab over 0.50 sqm. (DSR- 8.2.2.2)	2.52	Sqm		
23	Providing and fixing aluminium pull bolt lock, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade, with necessary screws bolts, nut and washers etc. complete.(DSR- 9.98)	4.00	Each		
24	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes. 110 mm diameter (DSR- 12.41.2)	20.00	Mtr		
25	Providing and fixing unplasticised - PVC pipe clips of approved design to unplasticised - PVC rain water pipes by means of 50x50x50 mm hard wood plugs, screwed with M.S. screws of required length,including cutting brick work and fixing in cement mortar 1:4 (1 cement: 4 coarse sand) and making good the wall etc. complete. 110 mm (DSR- 12.43.2)	10.00	Each		

26	Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion. Bend 87.5° 110 mm bend (DSR- 12.42.5.2)	5.00	Each		
27	Providing and fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS : 13592 Type A, including jointing with seal ring conforming to IS : 5382, leaving 10 mm gap for thermal expansion. Single tee with door 110x110x110 mm. (DSR- 12.42.3.2)	5.00	Each		
28	Making plinth protection 50 mm thick of cement concrete 1:3:6 (1cement: 3coarse sand : 6graded stone aggregate 20 mm nominal size) over 75mm thick bed of dry brick ballast 40 mm nominal size, well rammed and consolidated and grouted with fine sand, including finishing the top smooth. (DSR- 4.17)	13.20	Sqm		
<b>PART B (WATER SUPPLY &amp; SANITARY)</b>					
1	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, i/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer in Charge. Concealed work, including cutting chases and making good the walls etc. : 20 mm nominal outer dia Pipes (DSR 18.8.2)	15.00	Mtr		
2	Providing and fixing G.I. pipes complete with G.I. fittings including trenching and refilling etc. External work : 40 mm dia nominal bore. (DSR- 18.12.5)	10.00	Mtr		
3	Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931 : 15 mm nominal bore (DSR- 18.49.1)	2.00	Each		
4	Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430x260x350 mm and 340x410x265 mm sizes respectively with automatic flushing cistern with standard flush pipe and C.P. brass spreaders with brass unions and G.I clamps complete, including painting of fittings and brackets, cutting and making good the walls and floors wherever required : Range of two urinal basins with 5 litre white P.V.C. automatic flushing cistern. (DSR- 17.4.2)	3.00	Each		
5	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required : W.C. pan with ISI marked white solid plastic seat and lid W.C. pan with ISI marked black solid plastic seat and lid. (DSR- 17.2.2)	2.00	Each		

6	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require : White Vitreous China Wash basin size 550x400 mm with a pair of 15 mm C.P. brass pillar taps. (DSR-17.7.3)	3.00	Each		
7	Providing and fixing 600x450 mm beveled edge mirror of superior glass (of approved quality) complete with 6 mm thick hard board ground fixed to wooden cleats with C.P. brass screws and washers complete. (DSR- 17.31)	3.00	Each		
8	Providing and fixing 600x120x5 mm glass shelf with edges round off, supported on anodised aluminium angle frame with C.P. brass brackets and guard rail complete fixed with 40 mm long screws, rawl plugs etc., complete. (DSR- 17.33)	2.00	Each		
9	Providing and fixing PTMT liquid soap container 109 mm wide, 125 mm high and 112 mm distance from wall of standard shape with bracket of the same materials with snap fittings of approved quality and colour, weighing not less than 105 gms. (DSR- 17.71)	2.00	Each		
10	Providing and fixing PTMT towel rail complete with brackets fixed to wooden cleats with CP brass screws with concealed fittings arrangement of approved quality and colour. 450 mm long towel rail with total length of 495 mm, 78 mm wide and effective height of 88 mm, weighing not less than 170 gms (DSR- 17.73.1)	2.00	Each		
11	Providing and fixing uplasticised PVC connection pipe with brass unions : 30 cm length : 15 mm nominal bore (DSR- 18.21.1.1)	13.00	Mtr		
12	Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete. Semi rigid pipe 32 mm dia (DSR- 17.28.1.1)	13.00	Each		
13	Providing and placing on terrace (at all floor levels) polyethylene water storage tank, ISI : 12701 marked, with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank. (DSR-18.48)	1000.00	Ltr		
14	Constructing brick masonry chamber for underground C.I. inspection chamber and bends with bricks in cement mortar 1:4 (1 cement : 4 coarse sand) C.I. cover with frame (light duty) 455x610 mm internal dimensions, total weight of cover with frame to be not less than 38 kg (weight of cover 23 kg and weight of frame 15 kg), R.C.C. top slab with 1:2:4 mix (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size), foundation concrete 1:5:10 (1 cement : 5 fine sand : 10 graded stone aggregate 40 mm nominal size), inside plastering 12 mm thick with cement mortar 1:3 (1 cement : 3 coarse sand), finished smooth with a floating coat of neat cement on walls and bed concrete etc. complete as per standard design : Inside dimensions 455x610 mm and 45 cm deep for single pipe line : With common burnt clay F.P.S. (non modular) bricks of class designation 5 (DSR- 19.30.1.1 DR)	2.00	Each		
15	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end) :				

	40 mm nominal bore DSR-18.17.3	1.00	Nos		
16	Providing and fixing gun metal gate valve with C.I. wheel of approved quality (screwed end) :				
	20 mm nominal bore DSR-18.17.1A	2.00	Nos		
17	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931				
	15mm nominal bore DSR-18.53.1	5.00	Nos		
18	Providing and fixing PTMT grating of approved quality and colour. Circular type 100 mm nominal dia DSR-18.58.1.1	9.00	Nos		
	<b>PART C (ELECTRICAL PORTION)</b>				
1	Supplying and fixing following piano type switch/ socket on the existing switch box/ cover including connections etc. as required. 5/6 amps switch. (CPWD E&M SOR-2022, Item No. 1.23.1)	5.00	Each		
2	Wiring for light point/ fan point/ exhaust fan point/ call bell point with 1.5 sq.mm FRLS PVC insulated copper conductor single core cable in surface / recessed medium class PVC conduit, with piano type switch, phenolic laminated sheet, suitable size M.S. box and earthing the point with 1.5 sq.mm. FRLS PVC insulated copper conductor single core cable etc. as required. Group A. (CPWD E&M SOR-2022, Item No. 1.8.1)	5.00	Point		
3	Supplying and fixing following piano type switch/ socket on the existing switch box/ cover including connections etc. as required. 3 pin 5/6 amp socket outlet. (CPWD E&M SOR22, Item No. 1.23.4)	5.00	Each		
4	Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FRLS PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required. 2 X 1.5 sq. mm + 1 X 1.5 sq. mm earth wire. (CPWD E&M SOR-2022, Item No. 1.14.1)	50.00	Metre		
5	Supply and fixing of PVC board size 4"x4" with parpex sheet cover (75 mm x 75 mm x 50 mm)	5.00	No.		
6	Providing and fixing of 20 watt LED tube with box type fitting as per instruction of EIC.	5.00	No.		
7	Providing and fixing of Exhaust fan 230 mm as per instruction of EIC.	7.00	No.		
					<b>Total =</b>